



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

LOCTITE EA 9492 A

SDS No. : 204340

V011.0

Revision: 03.06.2024

printing date: 04.06.2024

Replaces version from: 06.11.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 9492 A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component epoxy adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website [www.mysds.henkel.com](http://www.mysds.henkel.com) or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

##### Hazard pictogram:



Contains

Bisphenol A Diglycidyl Ether

	Bisphenol-F epichlorhydrin resin; MW<700
<b>Signal word:</b>	Warning
<b>Hazard statement:</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
<b>Supplemental information</b>	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Precautionary statement: Prevention</b>	P273 Avoid release to the environment. P280 Wear protective gloves.
<b>Precautionary statement: Response</b>	P302+P352 IF ON SKIN: Wash with plenty of soap and water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

None if used properly.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Bisphenol-F epichlorhydrin resin; MW<700 ----- 701-263-0 01-2119454392-40	25- 50 %	Skin Irrit. 2, Dermal, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
Bisphenol A Diglycidyl Ether 1675-54-3 216-823-5 01-2119456619-26	10- 20 %	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Eye Irrit. 2; H319; C $\geq$ 5 % Skin Irrit. 2; H315; C $\geq$ 5 %	
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	1- < 5 %	Carc. 2, Inhalation, H351		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.

Obtain medical attention if irritation persists.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

EYE: Irritation, conjunctivitis.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media:**

water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

### 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet.

**7.3. Specific end use(s)**

2-Component epoxy adhesive

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

**Occupational Exposure Limits**

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC]		10	Time Weighted Average (TWA):		IR_OEL
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC]		0,8	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	aqua (freshwater)		0,003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	aqua (marine water)		0,0003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	sewage treatment plant (STP)		10 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	sediment (freshwater)				0,294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	sediment (marine water)				0,0294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Soil				0,237 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	aqua (intermittent releases)		0,0254 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Air						no hazard identified
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Predator						no potential for bioaccumulation
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	aqua (freshwater)		0,006 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Freshwater - intermittent		0,018 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	aqua (marine water)		0,001 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Marine water - intermittent		0,002 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	sewage treatment plant (STP)		10 mg/l				
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	sediment (freshwater)				0,341 mg/kg		
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	sediment (marine water)				0,034 mg/kg		
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Air						no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	Soil				0,065 mg/kg		
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane 1675-54-3	oral				11 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m <sup>3</sup>	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Workers	dermal	Acute/short term exposure - local effects		0,0083 mg/cm <sup>2</sup>	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m <sup>3</sup>	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m <sup>3</sup>	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m <sup>3</sup>	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
2,2'-[(1-Methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m <sup>3</sup>	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m <sup>3</sup>	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	grey, opaque
Odor	odourless
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	$< -15\text{ °C}$ ( $< 5\text{ °F}$ )
Initial boiling point	$> 260,0\text{ °C}$ ( $> 500\text{ °F}$ )
Flammability	Not applicable Non flammable product (flash point is greater than $93\text{ °C}$ )
Explosive limits	Not applicable, The product is not flammable.
Flash point	$> 248,0\text{ °C}$ ( $> 478.4\text{ °F}$ )
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	$> 260\text{ °C}$ ( $> 500\text{ °F}$ );
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) ( $25\text{ °C}$ ( $77\text{ °F}$ ); )	$7.051\text{ mm}^2/\text{s}$
Viscosity, dynamic (Cone and plate; $25\text{ °C}$ ( $77\text{ °F}$ ))	$10.000 - 20.000\text{ mPa.s}$ LCT STM 738; Rheological Data from flow curves
Solubility (qualitative) ( $20\text{ °C}$ ( $68\text{ °F}$ ); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure ( $20\text{ °C}$ ( $68\text{ °F}$ ))	Mixture $< 0,0300000\text{ mbar}$
Density ( $25\text{ °C}$ ( $77\text{ °F}$ ))	$1,5200 - 1,5600\text{ g/cm}^3$ None
Relative vapour density: ( $20\text{ °C}$ )	$> 1$
Particle characteristics	Not applicable Product is a liquid

### 9.2. Other information

Other information not applicable for this product

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Reaction with strong acids.  
Reacts with strong oxidants.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

Stable under normal conditions of storage and use.

**10.5. Incompatible materials**

See section reactivity.

**10.6. Hazardous decomposition products**

carbon oxides.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
Bisphenol A Diglycidyl Ether 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol A Diglycidyl Ether 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified



**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Bisphenol A Diglycidyl Ether 1675-54-3	moderately irritating	24 h	rabbit	Draize Test
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Bisphenol A Diglycidyl Ether 1675-54-3	slightly irritating		rabbit	Draize Test
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bisphenol A Diglycidyl Ether 1675-54-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Type of study / Route of administration</b>	<b>Metabolic activation / Exposure time</b>	<b>Species</b>	<b>Method</b>
Bisphenol-F epichlorhydrin resin; MW<700 -----	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Bisphenol A Diglycidyl Ether 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Bisphenol A Diglycidyl Ether 1675-54-3	negative with metabolic activation	mammalian cell gene mutation assay	with and without		not specified
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		mouse	not specified
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		rat	OECD Guideline 488 (In Vivo Transgenic Cell Gene Mutation Assays)
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		mouse	not specified
Bisphenol A Diglycidyl Ether 1675-54-3	negative	oral: gavage		mouse	not specified
Titanium dioxide 13463-67-7	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Bisphenol A Diglycidyl Ether 1675-54-3	not carcinogenic	oral: gavage	24 m daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Bisphenol A Diglycidyl Ether 1675-54-3	not carcinogenic	dermal	2 y 3 times/w	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOAEL P > 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Bisphenol A Diglycidyl Ether 1675-54-3	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol A Diglycidyl Ether 1675-54-3	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol A Diglycidyl Ether 1675-54-3	NOAEL 100 mg/kg	dermal	13 w 3 times/w	mouse	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains / surface water / ground water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	LC50	5,7 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol A Diglycidyl Ether 1675-54-3	LC50	1,2 mg/l	96 h	Oncorhynchus mykiss	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	2,7 mg/l	48 h	Daphnia magna	other guideline:
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol A Diglycidyl Ether 1675-54-3	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	other guideline:
Bisphenol A Diglycidyl Ether 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	other guideline:
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Bisphenol A Diglycidyl Ether 1675-54-3	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

#### 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Bisphenol A Diglycidyl Ether 1675-54-3	not inherently biodegradable	not specified	12 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Bisphenol A Diglycidyl Ether 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Bisphenol-F epichlorhydrin resin; MW<700 -----	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Bisphenol A Diglycidyl Ether 1675-54-3	> 2,64 - 3,78	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

#### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Bisphenol-F epichlorhydrin resin; MW<700 -----	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Bisphenol A Diglycidyl Ether 1675-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.

#### 12.6. Endocrine disrupting properties

not applicable

#### 12.7. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information****14.1. UN number or ID number**

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

**14.2. UN proper shipping name**

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

**14.3. Transport hazard class(es)**

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

**14.4. Packing group**

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

**14.5. Environmental hazards**

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	Environmentally Hazardous

**14.6. Special precautions for user**

ADR	not applicable
-----	----------------



	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3,00 %

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 27

LOCTITE EA 9492 B

SDS No. : 204341

V013.0

Revision: 03.06.2024

printing date: 04.06.2024

Replaces version from: 30.11.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 9492 B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy Hardener

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website [www.mysds.henkel.com](http://www.mysds.henkel.com) or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Acute toxicity	Category 2
H330 Fatal if inhaled.	
Route of Exposure: Inhalation	
Skin corrosion	Sub-category 1B
H314 Causes severe skin burns and eye damage.	
Serious eye damage	Category 1
H318 Causes serious eye damage.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Toxic to reproduction	Category 1B
H360F May damage fertility.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:**



**Contains**

Diethylenetriamine  
m-Phenylenebis(methylamine)  
4,4'-Isopropylidenediphenol  
benzyl alcohol  
N-(3-(Trimethoxysilyl)propyl)ethylenediamine  
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-, homopolymer

**Signal word:**

**Danger**

**Hazard statement:**

H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H330 Fatal if inhaled.  
H335 May cause respiratory irritation.  
H360F May damage fertility.  
H410 Very toxic to aquatic life with long lasting effects.

**Supplemental information**

EUH071 Corrosive to the respiratory tract.  
Restricted to professional users.

**Precautionary statement:  
Prevention**

P201 Obtain special instructions before use.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P260 Do not breathe vapours.

**Precautionary statement:  
Response**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**2.3. Other hazards**

None if used properly.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

4,4'-Isopropylidenediphenol 80-05-7	ED
nonylphenol 25154-52-3	ED

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Diethylenetriamine 111-40-0 203-865-4 01-2119473793-27	25- 50 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Acute Tox. 2, Inhalation, H330 STOT SE 3, H335 Eye Dam. 1, H318	inhalation:ATE = 0,071 mg/l;dust/mist	
m-Phenylenebis(methylamine) 1477-55-0 216-032-5 01-2119480150-50	5- < 10 %	Acute Tox. 4, Oral, H302 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Acute Tox. 4, Inhalation, H332 Aquatic Chronic 3, H412 Eye Dam. 1, H318		
4,4'-Isopropylidenediphenol 80-05-7 201-245-8 01-2119457856-23	1- < 5 %	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 10 ===== oral:ATE = 2.500 mg/kg	SVHC ED EU OEL
benzyl alcohol 100-51-6 202-859-9 01-2119492630-38	1- < 5 %	Acute Tox. 4, Oral, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	dermal:ATE = 2.500 mg/kg oral:ATE = 1.200 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylene diamine 1760-24-3 217-164-6 01-2119970215-39	0,1- < 1 %	Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 4, Inhalation, H332 STOT RE 2, Inhalation, H373	inhalation:ATE = 1,49 mg/l;dust/mist	
nonylphenol 25154-52-3 246-672-0	0,1- < 1 %	Aquatic Acute 1, H400 Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302 Repr. 2, H361fd Aquatic Chronic 1, H410	M acute = 10 M chronic = 10	SVHC ED
Titanium dioxide 13463-67-7 236-675-5 01-2119489379-17	0,1- < 1 %	Carc. 2, Inhalation, H351		
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-, homopolymer 29226-47-9	0,01- < 0,1 %	Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 4, Inhalation, H332 STOT RE 2, Inhalation, H373	inhalation:ATE = 1,49 mg/l;dust/mist	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.  
For full text of the H - statements and other abbreviations see section 16 "Other information".

**SECTION 4: First aid measures****4.1. Description of first aid measures**

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:  
Rinse with running water and soap.  
Obtain medical attention if irritation persists.

Eye contact:  
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:  
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**  
Causes burns.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

SKIN: Rash, Urticaria.

**4.3. Indication of any immediate medical attention and special treatment needed**  
See section: Description of first aid measures

## SECTION 5: Firefighting measures

**5.1. Extinguishing media**  
**Suitable extinguishing media:**  
water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**  
High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**  
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**  
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**  
In case of fire, keep containers cool with water spray.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**  
Avoid contact with skin and eyes.  
Wear protective equipment.  
Ensure adequate ventilation.  
Keep away from sources of ignition.

**6.2. Environmental precautions**  
Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**  
Dispose of contaminated material as waste according to Section 13.  
For small spills wipe up with paper towel and place in container for disposal.  
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**  
See advice in section 8

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Avoid skin and eye contact.  
See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.  
Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in sealed original container.  
Store in a cool, well-ventilated place.  
Refer to Technical Data Sheet.

**7.3. Specific end use(s)**

Epoxy Hardener

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
2,2'-Iminodi(ethylamine) 111-40-0 [2,2'-IMINODI(ETHYLAMINE)]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
2,2'-Iminodi(ethylamine) 111-40-0 [2,2'-IMINODI(ETHYLAMINE)]	1	4,3	Time Weighted Average (TWA):		EH40 WEL
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A]		2	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL) (INHALABLE FRACTION)]		2	Time Weighted Average (TWA):	Indicative	ECTLV
4,4'-Isopropylidenediphenol 80-05-7 [Bisphenol A; 4,4'-Isopropylidenediphenol]		2	Time Weighted Average (TWA):		EU OELIII
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

**Occupational Exposure Limits**Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
2,2'-Iminodi(ethylamine) 111-40-0 [DIETHYLENE TRIAMINE]	1	4	Time Weighted Average (TWA):		IR_OEL
2,2'-Iminodi(ethylamine) 111-40-0 [DIETHYLENE TRIAMINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC]		10	Time Weighted Average (TWA):		IR_OEL
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) 14807-96-6 [TALC]		0,8	Time Weighted Average (TWA):		IR_OEL
m-Phenylenebis(methylamine) 1477-55-0 [M-XYLENE A,A'-DIAMINE (M-PHENYLENEBIS(METHYLAMINE))]		0,1	Time Weighted Average (TWA):		IR_OEL
m-Phenylenebis(methylamine) 1477-55-0 [M-XYLENE A,A'-DIAMINE (M-PHENYLENEBIS(METHYLAMINE))]		0,1	Time Weighted Average (TWA):		IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'-ISOPROPYLIDENEDIPHENOL)]		2	Time Weighted Average (TWA):	Indicative	ECTLV



(INHALABLE FRACTION)]					
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A (4,4'- ISOPROPYLIDENEDIPHENOL)]		2	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [Bisphenol A; 4,4'-Isopropylidenediphenol]		2	Time Weighted Average (TWA):		EU OELIII
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		10	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE]		4	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2,2'-iminodiethylamine 111-40-0	aqua (freshwater)		0,56 mg/l				
2,2'-iminodiethylamine 111-40-0	aqua (marine water)		0,056 mg/l				
2,2'-iminodiethylamine 111-40-0	aqua (intermittent releases)		0,32 mg/l				
2,2'-iminodiethylamine 111-40-0	sediment (freshwater)				1072 mg/kg		
2,2'-iminodiethylamine 111-40-0	sediment (marine water)				107,2 mg/kg		
2,2'-iminodiethylamine 111-40-0	sewage treatment plant (STP)		6 mg/l				
2,2'-iminodiethylamine 111-40-0	Soil				7,97 mg/kg		
2,2'-iminodiethylamine 111-40-0	Air						no hazard identified
m-Phenylenebis(methylamine) 1477-55-0	aqua (freshwater)		0,094 mg/l				
m-Phenylenebis(methylamine) 1477-55-0	aqua (marine water)		0,009 mg/l				
m-Phenylenebis(methylamine) 1477-55-0	Freshwater - intermittent		0,152 mg/l				
m-Phenylenebis(methylamine) 1477-55-0	sewage treatment plant (STP)		10 mg/l				
m-Phenylenebis(methylamine) 1477-55-0	sediment (freshwater)				12,4 mg/kg		
m-Phenylenebis(methylamine) 1477-55-0	sediment (marine water)				1,24 mg/kg		
m-Phenylenebis(methylamine) 1477-55-0	Soil				2,44 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	aqua (freshwater)		0,023 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (marine water)		0,019 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	Freshwater - intermittent		0,011 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sewage treatment plant (STP)		320 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sediment (freshwater)				1,2 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	sediment (marine water)				0,24 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Soil				3,7 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Air						no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Predator						no potential for bioaccumulation
Benzyl alcohol 100-51-6	Soil				0,456 mg/kg		
Benzyl alcohol 100-51-6	sewage treatment plant (STP)		39 mg/l				
Benzyl alcohol 100-51-6	sediment (freshwater)				5,27 mg/kg		
Benzyl alcohol 100-51-6	sediment (marine water)				0,527 mg/kg		
Benzyl alcohol 100-51-6	aqua (marine water)		0,1 mg/l				
Benzyl alcohol 100-51-6	aqua (intermittent releases)		2,3 mg/l				

Benzyl alcohol 100-51-6	aqua (freshwater)		1 mg/l				
Benzyl alcohol 100-51-6	Predator						no potential for bioaccumulation
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	aqua (freshwater)		0,05 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	aqua (marine water)		0,005 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Freshwater - intermittent		0,072 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sediment (freshwater)				0,181 mg/kg		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sediment (marine water)				0,018 mg/kg		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Soil				0,007 mg/kg		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sewage treatment plant (STP)		20 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-iminodiethylamine 111-40-0	Workers	dermal	Long term exposure - systemic effects		11,4 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	dermal	Long term exposure - local effects		1,1 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Acute/short term exposure - systemic effects		92,1 mg/m3	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Acute/short term exposure - local effects		2,6 mg/m3	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Long term exposure - systemic effects		15,4 mg/m3	no hazard identified
2,2'-iminodiethylamine 111-40-0	Workers	Inhalation	Long term exposure - local effects		0,87 mg/m3	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	dermal	Acute/short term exposure - systemic effects		4,88 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	Inhalation	Acute/short term exposure - systemic effects		27,5 mg/m3	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	dermal	Long term exposure - systemic effects		4,88 mg/kg	no hazard identified
2,2'-iminodiethylamine 111-40-0	General population	Inhalation	Long term exposure - systemic effects		4,6 mg/m3	no hazard identified
m-Phenylenebis(methylamine) 1477-55-0	Workers	dermal	Long term exposure - systemic effects		0,33 mg/kg	
m-Phenylenebis(methylamine) 1477-55-0	Workers	inhalation	Long term exposure - systemic effects		1,2 mg/m3	
m-Phenylenebis(methylamine) 1477-55-0	Workers	inhalation	Long term exposure - local effects		0,2 mg/m3	
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Acute/short term exposure - systemic effects		0,031 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Long term exposure - systemic effects		0,031 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Long term exposure - systemic effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Long term exposure - systemic effects		0,002 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	Inhalation	Long term exposure - systemic effects		1 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Long term exposure - local effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Acute/short term exposure - local effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - systemic effects		1 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Long term exposure - local		1 mg/m3	no hazard identified

			effects			
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - local effects		1 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Acute/short term exposure - systemic effects		0,002 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Long term exposure - systemic effects		0,004 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Acute/short term exposure - systemic effects		0,004 mg/kg	no hazard identified
Benzyl alcohol 100-51-6	General population	oral	Acute/short term exposure - systemic effects		20 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	oral	Long term exposure - systemic effects		4 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	inhalation	Acute/short term exposure - systemic effects		110 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	inhalation	Long term exposure - systemic effects		22 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	inhalation	Acute/short term exposure - systemic effects		27 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	inhalation	Long term exposure - systemic effects		5,4 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	dermal	Acute/short term exposure - systemic effects		40 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	dermal	Long term exposure - systemic effects		8 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	dermal	Acute/short term exposure - systemic effects		20 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	dermal	Long term exposure - systemic effects		4 mg/kg	no potential for bioaccumulation
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Long term exposure - systemic effects		130 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Acute/short term exposure - local effects		5,36 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Long term exposure - systemic effects		26 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	oral	Long term exposure - systemic effects		4 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Acute/short term exposure - local effects		4 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Long term exposure - local effects		0,6 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Long term exposure - local effects		0,1 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Acute/short term exposure - systemic effects		26400 mg/m <sup>3</sup>	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Long term exposure - local effects			
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Acute/short term exposure - local effects			

N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Long term exposure - local effects			
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Acute/short term exposure - local effects			
Titanium dioxide 13463-67-7	Workers	inhalation	Long term exposure - local effects		0,17 mg/m3	
Titanium dioxide 13463-67-7	General population	inhalation	Long term exposure - local effects		0,028 mg/m3	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

## Engineering controls:

Ensure good ventilation/extraction.

## Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

## Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to &gt; 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to &gt; 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

## Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

## Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

## Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Delivery form

liquid

Colour

grey, opaque

Odor

characteristic, Of

amine

Physical state

liquid

Melting point

Not applicable, Product is a liquid

Solidification temperature

&lt; -15 °C (&lt; 5 °F)

Initial boiling point	> 140 °C (> 284 °F)
Flammability	Not applicable Non flammable product (flash point is greater than 93°C)
Explosive limits	Not applicable, The product is not flammable.
Flash point	> 100,0 °C (> 212 °F); no method / method unknown
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	> 200 °C (> 392 °F);
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (25 °C (77 °F); )	> 20 mm <sup>2</sup> /s
Viscosity, dynamic (Cone and plate; 25 °C (77 °F); Shear gradient: 40 s-1)	20 - 45 mPa.s LCT STM 738; Rheological Data from flow curves
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Partially soluble
Partition coefficient: n-octanol/water	Not applicable Mixture
Vapour pressure (50 °C (122 °F))	< 1,3300000 mbar
Vapour pressure (20 °C (68 °F))	< 1,3300000 mbar
Density (25 °C (77 °F))	1,5000 - 1,5800 g/cm <sup>3</sup> None
Relative vapour density: (20 °C)	> 1
Particle characteristics	Not applicable Product is a liquid

## 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with strong oxidants.  
Acids.  
Reaction with strong acids.  
Strong bases.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.  
Rapid polymerisation may generate excessive heat and pressure.  
May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diethylenetriamine 111-40-0	LD50	1.553 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
m- Phenylenebis(methylamin e) 1477-55-0	LD50	980 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	LD50	> 2.000 - < 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	1.200 mg/kg		Expert judgement
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LD50	2.295 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)
nonylphenol 25154-52-3	LD50	1.900 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Titanium dioxide 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
1,2-Ethanediamine, N1- [3- (trimethoxysilyl)propyl]-, homopolymer 29226-47-9	LD50	2.295 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)



**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Diethylenetriamine 111-40-0	LD50	1.045 mg/kg	rabbit	not specified
m- Phenylenebis(methylamin e) 1477-55-0	LD50	> 3.100 mg/kg	rat	not specified
4,4'- Isopropylidenediphenol 80-05-7	LD50	3.000 mg/kg	rabbit	not specified
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LD50	> 2.000 mg/kg	rat	EPA OPPTS 870.1200 (Acute Dermal Toxicity)
nonylphenol 25154-52-3	LD50	> 2.000 mg/kg	rabbit	not specified
Titanium dioxide 13463-67-7	LD50	> 10.000 mg/kg	rabbit	not specified
1,2-Ethanediamine, N1- [3- (trimethoxysilyl)propyl]-, homopolymer 29226-47-9	LD50	> 2.000 mg/kg	rat	EPA OPPTS 870.1200 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Diethylenetriamine 111-40-0	LD 50	> 0,07 - < 0,30 mg/l		4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Diethylenetriamine 111-40-0	Acute toxicity estimate (ATE)	0,071 mg/l	dust/mist			Expert judgement
m- Phenylenebis(methylamin e) 1477-55-0	LC50	1,34 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
benzyl alcohol 100-51-6	LC50	> 5,4 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	LC50	1,49 - 2,44 mg/l	dust/mist	4 h	rat	EPA OPPTS 870.1300 (Acute inhalation toxicity)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	Acute toxicity estimate (ATE)	1,49 mg/l	dust/mist			Expert judgement
Titanium dioxide 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
1,2-Ethanediamine, N1- [3- (trimethoxysilyl)propyl]-, homopolymer 29226-47-9	Acute toxicity estimate (ATE)	1,49 mg/l	dust/mist			Expert judgement

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diethylenetriamine 111-40-0	corrosive	15 min	rabbit	BASF Test
benzyl alcohol 100-51-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
N-(3- (Trimethoxysilyl)propyl)e thylenediamine 1760-24-3	mildly irritating	4 h	rabbit	EPA OPPTS 870.2500 (Acute Dermal Irritation)
nonylphenol 25154-52-3	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Diethylenetriamine 111-40-0	corrosive	30 s	rabbit	not specified
benzyl alcohol 100-51-6	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
nonylphenol 25154-52-3	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Diethylenetriamine 111-40-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
m-Phenylenebis(methylamine) 1477-55-0	Sub-Category 1B (sensitising)	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
4,4'-Isopropylidenediphenol 80-05-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 406 (Skin Sensitisation)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Sub-Category 1A (sensitising)	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
nonylphenol 25154-52-3	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
nonylphenol 25154-52-3	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Titanium dioxide 13463-67-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Type of study / Route of administration</b>	<b>Metabolic activation / Exposure time</b>	<b>Species</b>	<b>Method</b>
Diethylenetriamine 111-40-0	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Diethylenetriamine 111-40-0	negative	in vitro mammalian chromosome aberration test	with and without		Chromosome Aberration Test
m- Phenylenebis(methylamin e) 1477-55-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
m- Phenylenebis(methylamin e) 1477-55-0	negative	in vitro mammalian chromosome aberration test	with and without		not specified
4,4'- Isopropylidenediphenol 80-05-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
benzyl alcohol 100-51-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
nonylphenol 25154-52-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Ames Test
Titanium dioxide 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	in vitro mammalian cell micronucleus test	without		equivalent or similar to OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous components CAS-No.</b>	<b>Result</b>	<b>Route of application</b>	<b>Exposure time / Frequency of treatment</b>	<b>Species</b>	<b>Sex</b>	<b>Method</b>
Diethylenetriamine 111-40-0	not carcinogenic	dermal	lifetime (appr. 587 d) 3 d/w	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
benzyl alcohol 100-51-6	not carcinogenic	oral: gavage	104 weeks once daily, 5 days/week	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
Titanium dioxide 13463-67-7	not carcinogenic	oral: feed	103 w daily	rat	male/female	not specified

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Diethylenetriamine 111-40-0	NOAEL P 100 mg/kg NOAEL F1 30 mg/kg	screening	oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
4,4'- Isopropylidenediphenol 80-05-7	NOAEL P 300 ppm		oral: feed	mouse	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
benzyl alcohol 100-51-6	NOAEL P 200 mg/kg	screening	oral: gavage	mouse	not specified
Titanium dioxide 13463-67-7	NOAEL P >= 1.000 mg/kg NOAEL F1 >= 1.000 mg/kg	one- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Diethylenetriamine 111-40-0	NOAEL 70 - 80 mg/kg	oral: feed	90 d daily	rat	not specified
Diethylenetriamine 111-40-0	NOAEL 0,55 mg/l	inhalation: vapour	15 d 6 h/d	rat	not specified
m- Phenylenebis(methylamin e) 1477-55-0	LOAEL >= 600 mg/kg	oral: gavage	28 days daily	rat	Guidelines for 28-Day Repeat Dose Toxicity Test (Japan)
benzyl alcohol 100-51-6	NOAEL 400 mg/kg	oral: gavage	13 weeks once daily, 5 days/week	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
nonylphenol 25154-52-3	NOAEL 100 mg/kg	oral: feed	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
Titanium dioxide 13463-67-7	NOAEL > 1.000 mg/kg	oral: gavage	92 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

**SECTION 12: Ecological information****General ecological information:**

Do not empty into drains / surface water / ground water.

**12.1. Toxicity****Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	LC50	430 mg/l	96 h	Poecilia reticulata	EU Method C.1 (Acute Toxicity for Fish)
Diethylenetriamine 111-40-0	NOEC	> 10 mg/l	28 d	Gasterosteus aculeatus	OECD Guideline 210 (fish early life stage toxicity test)
m-Phenylenebis(methylamine) 1477-55-0	LC50	87,6 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	LC50	4,6 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	LOEC	0,000372 mg/l	300 d	Danio rerio	OECD Guideline 234 (Fish Sexual Development Test)
benzyl alcohol 100-51-6	LC50	460 mg/l	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)
N-(3-(Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	LC50	168 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
nonylphenol 25154-52-3	LC50	0,23 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
nonylphenol 25154-52-3	NOEC	0,006 mg/l	91 d	not specified	OECD Guideline 210 (fish early life stage toxicity test)
Titanium dioxide 13463-67-7	LC50	Toxicity > Water solubility	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)

**Toxicity (aquatic invertebrates):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	EC50	64,6 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
m-Phenylenebis(methylamine) 1477-55-0	EC50	15,2 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	0,885 mg/l	48 h	Acartia clausi	other guideline:
benzyl alcohol 100-51-6	EC50	230 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N-(3-(Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	87,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
nonylphenol 25154-52-3	EC50	0,085 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEC	5,6 mg/l	21 d	Daphnia magna	EU Method C.20 (Daphnia magna Reproduction Test)
m-Phenylenebis(methylamine) 1477-55-0	NOEC	4,7 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'-Isopropylidenediphenol 80-05-7	LOEC	0,00025 mg/l	150 d	Marisa cornuarietis	other guideline:
benzyl alcohol 100-51-6	NOEC	51 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	NOEC	> 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
nonylphenol 25154-52-3	NOEC	0,024 mg/l	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	EC50	1.164 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Diethylenetriamine 111-40-0	NOEC	10 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
m-Phenylenebis(methylamine) 1477-55-0	EC50	33,3 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
m-Phenylenebis(methylamine) 1477-55-0	NOEC	22,9 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	3,73 mg/l	96 h	other:	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	2,1 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	EC50	770 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	NOEC	310 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	8,8 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	NOEC	3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
nonylphenol 25154-52-3	EC50	0,41 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
nonylphenol 25154-52-3	EC10	0,12 mg/l	96 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Diethylenetriamine 111-40-0	NOEC	6 mg/l	3 h	anaerobic bacteria	not specified
m-Phenylenebis(methylamine) 1477-55-0	EC50	> 1.000 mg/l	30 min	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	> 320 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
benzyl alcohol 100-51-6	EC10	658 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC 50	435 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
nonylphenol 25154-52-3	EC10	950 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)



Titanium dioxide 13463-67-7	EC0	Toxicity > Water solubility	24 h	Pseudomonas fluorescens	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
--------------------------------	-----	--------------------------------	------	-------------------------	--

## 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Diethylenetriamine 111-40-0	inherently biodegradable	aerobic	83 %	28 d	EU Method C.9 (Biodegradation: Zahn-Wellens Test)
Diethylenetriamine 111-40-0	readily biodegradable	aerobic	87 %	21 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
m-Phenylenebis(methylamine) 1477-55-0	not readily biodegradable.	aerobic	49 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
4,4'-Isopropylidenediphenol 80-05-7	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
benzyl alcohol 100-51-6	readily biodegradable	aerobic	92 - 96 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3		aerobic	50 %		OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)
nonylphenol 25154-52-3	not readily biodegradable.	aerobic	48,2 %	35 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

## 12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Diethylenetriamine 111-40-0	> 0,3 - < 6,3	42 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)
4,4'-Isopropylidenediphenol 80-05-7	5,1 - 67	42 d	25 °C	Cyprinus carpio	other guideline:
nonylphenol 25154-52-3	740			Pimephales promelas	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

**12.4. Mobility in soil**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Diethylenetriamine 111-40-0	-1,58	20 °C	QSAR (Quantitative Structure Activity Relationship)
m-Phenylenebis(methylamine) 1477-55-0	0,18	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
4,4'-Isopropylidenediphenol 80-05-7	3,4	21,5 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
benzyl alcohol 100-51-6	1,05	20 °C	EU Method A.8 (Partition Coefficient)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-1,67		not specified
nonylphenol 25154-52-3	5,4	23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

**12.5. Results of PBT and vPvB assessment**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Diethylenetriamine 111-40-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
m-Phenylenebis(methylamine) 1477-55-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'-Isopropylidenediphenol 80-05-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
benzyl alcohol 100-51-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
nonylphenol 25154-52-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Titanium dioxide 13463-67-7	According to Annex XIII to Regulation (EC) No 1907/2006, a PBT and vPvB assessment shall not be conducted for inorganic substances.

**12.6. Endocrine disrupting properties**

not applicable

**12.7. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**Product disposal:**

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

**Disposal of uncleaned packages:**

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

**Waste code**

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

**SECTION 14: Transport information****14.1. UN number or ID number**

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

**14.2. UN proper shipping name**

ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylylenediamine,Diethylenetriamine)
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylylenediamine,Diethylenetriamine)
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylylenediamine,Diethylenetriamine)
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (m-Xylylenediamine,Diethylenetriamine,4,4'-Isopropylidenediphenol)
IATA	Amines, liquid, corrosive, n.o.s. (m-Xylylenediamine,Diethylenetriamine)

**14.3. Transport hazard class(es)**

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

**14.4. Packing group**

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

**14.5. Environmental hazards**

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable
-----	----------------

	Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	nonylphenol CAS 25154-52-3

Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3,00 %

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H360F May damage fertility.  
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

### Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,  
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**