

Features

- 3-5/6 digit, 6000 Counts LCD Display
- Manual & Auto Ranging
- 30mm Jaw Capacity
- Diode and Continuity Test
- NCV Detector
- **Continuity Buzzer**

- · Data Hold
- MAX/MIN & Relative Mode
- · Auto Power Off
- Low Battery Indication
- Input Protection
- Input Impedance for DCV: 10MΩ

Electrical Specifications

Basic Functions	Range	Best Accuracy
AC Current	6A/60A/600A	±(2.5% +5 digits)
AC Voltage	6V/60V/600V/750V	±(1.2% +5 digits)
DC Voltage	600mV/6V/60V/600V/1000V	±(0.8% +1 digit)
Resistance	600Ω/6ΚΩ/60ΚΩ/600ΚΩ/6ΜΩ/60ΜΩ	±(1% +2 digits)
Capacitance	99.99nF/999.9nF/9.999µF/99.99µF/999.9µF/9.999mF/59.99mF	±(4% +5 digits)
Jaw Capacity	30mm	
Auto Power Off	Around 15 minutes	
Low Battery Indication	< 3.6V	

General Characteristics

Safety Rating	: CAT II 10	00V, CAT III 600V	
Power	: AAA 1.5V	/ Batteries × 3	
LCD Size	: 38mm × 24mm		
Product Colour	: Green &	Grey	
Product Weight	: 280g		
Product Size	· 220mm ×	: 75mm × 40mm	
Accessories	Qty.	Note	
	1	······	
Accessories	Qty.	······	

Part Number Table

Description	Part Number
True RMS Digital Clamp Meter, 30mm Jaw	72-3097

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

