



# Direct online starter, TeSys island, 15A AC-1, 9A AC-3, 4kW / 5hp

Local distributor code:

425225486 TPRST009

EAN Code: 3606489832742

## Main

Range	TeSys
Product name	TeSys island
Device short name	TPRST
Product or component type	Motor starter
Motor starter type	Direct on line
Device presentation	Direct starter connected to an automation controller through a bus coupler Operational only when connected to a bus coupler
Function available	Upstream voltage presence detection Electrical line and load protection Power and energy monitoring when connected with TPRVM voltage module
Product compatibility	TPRBC bus coupler TPRVM voltage interface module
Poles description	3P (3 NO)
Utilisation category	AC-1 AC-2 AC-3 AC-4 AC-3e
Motor power kW	2.2 kW at 230 V 50 Hz (AC-3) 4 kW at 380415 V 50 Hz (AC-3) 4 kW at 440 V 50 Hz (AC-3) 5.5 kW at 500 V 50 Hz (AC-3) 5.5 kW at 690 V 50 Hz (AC-3)
motor power HP (UL / CSA)	0.33 hp at 120 V AC 60 Hz for 1 phase motors  1 hp at 240 V AC 60 Hz for 1 phase motors  2 hp at 208 V AC 60 Hz for 3 phases motors  2 hp at 240 V AC 60 Hz for 3 phases motors  5 hp at 480 V AC 60 Hz for 3 phases motors  7.5 hp at 600 V AC 60 Hz for 3 phases motors
[Ue] rated operational voltage	<= 690 V AC 4763 Hz
[le] rated operational current	9 A (at <50 °C) at <= 440 V AC-3 15 A (at <50 °C) at <= 440 V AC-1
[Ith] conventional free air thermal current	15 A (at 50 °C)
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1 600 V conforming to UL 60947-4-1 600 V conforming to CSA C22.2 No 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1
Overvoltage category	III
Thermal protection adjustment range	0.189 A
Thermal overload class	Class 530

Reset	Remotely or automatically
Irms rated making capacity	250 A at 440 V conforming to IEC 60947
Rated breaking capacity	250 A at 440 V conforming to IEC 60947
[lcw] rated short-time withstand current	210 A 40 °C - 1 s 105 A 40 °C - 10 s 61 A 40 °C - 1 min 30 A 40 °C - 10 min
Average impedance	2.5 mOhm - Ith 15 A 50 Hz
Power dissipation per pole	0.2 W AC-3 - Ith 9 A 0.56 W AC-1 - Ith 15 A
[Uc] control circuit voltage	24 V DC supplied by the bus coupler
Current consumption	160 mA contactor sealed 160 mA contactor closing
Power dissipation in W	3.5 W at le AC-3

## Complementary

Mechanical durability	30 Mcycles
Electrical durability	2 Mcycles 9 A AC-3 at Ue 440 V
	1.2 Mcycles 15 A AC-1 at Ue 440 V
Maximum operating rate	3600 cyc/mn AC-3
Operating time	< 100 ms closing
	< 30 ms opening
Safety performance level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Protection type	Thermal overload protection
	Motor overheat
	Overcurrent
	Undercurrent
	Jam
	Long start
	Stall
	Rapid cycle lockout
	Phase sequence
	Rapid restart lockout
	Phase reversal
	Phase loss
	Phase unbalance
	Ground current
Monitoring type	Time device ON
	Time device switch ON
	Number of faults
	Number of switching cycles
	Number of device power cycles
	Average current lavg
	Average voltage Vavg
	Max current Imax
	Max current max  Max voltage Vmax
	Active and reactive power with voltage module
	Active and reactive power with voltage module  Active and reactive energy with voltage module
	True power factor with voltage module
Local signalling	1 LED (green/red) for DS (device status)
	1 LED (green/red) for LS (load status)
Standards	EN/IEC 60947-1
	EN/IEC 60947-4-1
	UL 60947-4-1
	CSA C22.2 No 60947-4-1
Product certifications	EAC
	CSA
	CCC
	10

UL

Mounting mode	Horizontal and vertical (35 mm symmetrical DIN rail)
Connections - terminals	Screw-clamp terminals 1 cable(s) 14 mm² (AWG 16AWG 12) rigid
	Screw-clamp terminals 2 cable(s) 14 mm² (AWG 16AWG 12) rigid
	Screw-clamp terminals 1 cable(s) 1.54 mm² (AWG 16AWG 12) flexible without cable end
	Screw-clamp terminals 2 cable(s) 1.54 mm² (AWG 16AWG 12) flexible without cable end
	Screw-clamp terminals 1 cable(s) 14 mm² (AWG 16AWG 12) flexible with cable end
	Screw-clamp terminals 2 cable(s) $12.5 \text{ mm}^2$ (AWG 16AWG 14) flexible with cable end
Tightening torque	1.7 N.m - with screwdriver flat Ø 6 mm
	1.7 N.m - with screwdriver Philips No 2
Width	45 mm
Height	116 mm
Depth	115 mm
Net weight	0.656 kg

## **Environment**

Ambient air temperature for storage	-2570 °C	
Ambient air temperature for operation	-1050 °C without derating 5060 °C with current derating	
Relative humidity	595 %	
Operating altitude	02000 m without derating	
IP degree of protection	IP20	
Pollution degree	2	
Protective treatment	TC	
Fire resistance	960 °C conforming to UL 94 850 °C conforming to IEC 60695-2-1 650 °C conforming to IEC 60695-2-12	
Shock resistance	15 gn (duration = 11 ms) conforming to IEC 60068-2-27	
Vibration resistance	1.5 mm peak to peak (f= 313 Hz) conforming to IEC 60068-2-6 1 gn (f= 13200 Hz) conforming to IEC 60068-2-6	
Electromagnetic compatibility	Electrostatic discharge immunity test, level 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF field immunity test, level 3, 10 V/m, conforming to EN/IEC 61000-4-3 Fast transient immunity test, level 4, 4 kV, conforming to EN/IEC 61000-4-4 Surge immunity test (differential mode), level 3, 2 kV, conforming to EN/IEC 61000-4-5 Surge immunity test (common mode), level 4, 4 kV, conforming to EN/IEC 61000-4-5 Conducted RF disturbance immunity test, 20 V, conforming to EN/IEC 61000-4-6	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	12.5 cm
Package 1 Length	13.0 cm
Package 1 Weight	709.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	14

Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	10.252 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information