

#### Part Number : 150670604

Product Description : 1.00mm Pitch Premo-Flex Hot Bar Solder FFC Jumpers, Same Side Contacts (Type A), 152.00mm Cable Length, Tin (Sn) Plating, 4 Circuits

Series Number : 15067

Status : Active

Product Category : Flexible Printed Circuit (FPC) Flex Jumpers

#### **Documents & Resources**

Drawings 150670604\_sd.pdf

Specifications 150670001-000.pdf

### **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <b>©</b>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21             |
| REACH SVHC         | Not Contained per D(2024)4144-DC<br>(27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                          |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474



## - chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## Part Details

## General

| Status         | Active  |
|----------------|---|
| Category       | Flexible Printed Circuit (FPC) Flex<br>Jumpers  |
| Series         | 15067   |
| Description    | 1.00mm Pitch Premo-Flex Hot Bar<br>Solder FFC Jumpers, Same Side<br>Contacts (Type A), 152.00mm Cable<br>Length, Tin (Sn) Plating, 4 Circuits |
| Comments       | Contacts on the same side, Type A   |
| Product Family | FFC Cable Jumpers, Premo-Flex<br>Flat-Flexible Cable Jumpers  |
| Product Name   | Premo-Flex Hot Bar Solder FFC<br>Jumper   |
| UPC            | 196823685859  |

## Electrical

| Current - Maximum per Contact | 1.25A  |
|-------------------------------|--------|
| Voltage - Maximum             | 60V AC |

# Physical

| Cable Length                  | 152.00mm        |
|-------------------------------|-----------------|
| Circuits (Loaded)             | 4               |
| Contact Layout Type           | A (same side)   |
| Design Feature                | Direct to Board |
| Material - Plating Mating     | Tin             |
| Packaging Type                | Bag             |
| Pitch - Mating Interface      | 1.00mm          |
| Temperature Range - Operating | -40° to +105°C  |
| Termination Style             | Solder          |
| Wire/Cable Type               | Flat Flex Cable |
| Wire Size (AWG)               | N/A             |

This document was generated on Nov 04, 2024