



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

Contains Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)1,3-propanediol (4:1), 2-hydroxy-3-mercaptoppropyl ether; Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW



SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

Signal word

Warning

Hazard statements

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P261 - Avoid breathing fumes
P264 - Wash face, hands and any exposed skin thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention
P391 - Collect spillage
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Toxic to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether 20 - 25 %	615-735-8	72244-98-5	Skin Sens. 1B (H317) Aquatic Chronic 3 (H412)	-	-	-	Exempt
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 10 - <20 %	500-033-5	25068-38-6	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	-	-	01-2119456619-26-xxxx
Copper flakes (coated with aliphatic acid) 1 - <2.5 %	231-159-6 (029-024-00-X)	7440-50-8	Eye Irrit. 2 (H319) Acute Tox. 4 (H302) Acute Tox. 3 (H331) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	10	10	01-2119480154-42-xxxx
2,4,6-tris(dimethylamino methyl)phenol	202-013-9 (603-069-00-	90-72-2	Acute Tox. 4 (H302) Skin Irrit. 2 (H315)	-	-	-	01-2119560597-27-XXXX

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

1 - <2.5 %	0)		Eye Irrit. 2 (H319)				
------------	----	--	---------------------	--	--	--	--

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE_{mix}) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl) 1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	615-735-8	72244-98-5	-	-	-	-	-
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	-	-	-	-	-
Copper flakes (coated with aliphatic acid)	231-159-6 (029-024-00-X)	7440-50-8	500	-	0.733	-	-
2,4,6-tris(dimethylaminoethyl)phenol	202-013-9 (603-069-00-0)	90-72-2	1999	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supercedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.
Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Hydrogen chloride. Nitrogen oxides (NOx). Sulphur oxides. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Recommended storage temperature Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Resin.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Talc 14807-96-6	-	TWA: 1 mg/m ³ STEL: 3 mg/m ³
Copper flakes (coated with aliphatic acid) 7440-50-8	-	TWA: 1 mg/m ³ TWA: 0.2 mg/m ³ STEL: 0.6 mg/m ³ STEL: 2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Copper flakes (coated with aliphatic acid) (7440-50-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	137 mg/kg bw/d	

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

worker Short term Systemic health effects	Dermal	273 mg/kg bw/d	
---	--------	----------------	--

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

Copper flakes (coated with aliphatic acid) (7440-50-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Local health effects	Inhalation	1 mg/m ³	
Consumer Long term Systemic health effects	Oral	0.041 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

Copper flakes (coated with aliphatic acid) (7440-50-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	7.8 µg/l
Marine water	5.2 µg/l
Microorganisms in sewage treatment	230 µg/l
Freshwater sediment	87 mg/kg dry weight
Marine sediment	676 mg/kg dry weight
Soil	65 mg/kg dry weight

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

	breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Unsuitable gloves materials: Disposable gloves. Leather. Gloves must conform to standard EN 374
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	During spraying wear suitable respiratory equipment. In case of inadequate ventilation wear respiratory protection.
Recommended filter type:	Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	metallic Brown
Odour	Sulphurous. Pungent.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	None known
Autoignition temperature	No data available	Not applicable
Decomposition temperature	150 °C	
pH	.	Not applicable. Substance/mixture is non-polar/aprotic.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	Immiscible in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	1.96	
Bulk density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	11,868.50 mg/kg
ATEmix (dermal)	116,363.60 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	30.50 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	-
Copper flakes (coated with aliphatic acid)	-	-	> 5.11 mg/L (Rat) 4 h
2,4,6-tris(dimethylaminomethyl)phenol	=2169 mg/kg (Rattus)	> 1 ml/kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
 Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
 Revision Number 2.02

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		
Copper flakes (coated with aliphatic acid) 7440-50-8	EC50: 0.0426 - 0.0535mg/L (72h, Pseudokirchneriella subcapitata) EC50: 0.031 - 0.054mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 0.0068 - 0.0156mg/L (96h, Pimephales promelas)	-	EC50: =0.03mg/L (48h, Daphnia magna)	10	10
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	EC50 (72h) = 84 mg/L (Desmodesmus subspicatus) OECD 201	CL50 (96h) =175 mg/L (Cyprinus carpio)	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26
2,4,6-tris(dimethylaminomethyl)phenol	0.219

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	The substance is not PBT / vPvB
Copper flakes (coated with aliphatic acid)	The substance is not PBT / vPvB
2,4,6-tris(dimethylaminomethyl)phenol	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
Waste codes / waste designations according to EWC	15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN3077
14.2 UN proper shipping name	Environmentally hazardous substances, solid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes (coated with aliphatic acid))
14.3 Transport hazard class(es)	9
Labels	9
14.4 Packing group	III
Description	UN3077, Environmentally hazardous substances, solid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes (coated with aliphatic acid)), 9, III, (-)
14.5 Environmental hazards	Yes
14.6 Special precautions for user	
Special Provisions	274, 335, 601, 375
Classification code	M7
Tunnel restriction code	(-)
Limited quantity (LQ)	5 kg
ADR Hazard Id (Kemmler Number)	90

IMDG

14.1 UN number or ID number	UN3077
14.2 UN proper shipping name	Environmentally hazardous substances, solid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes (coated with aliphatic acid))
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3077, Environmentally hazardous substances, solid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes (coated with aliphatic acid)), 9, III, Marine pollutant
14.5 Marine pollutant	P

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

14.6 Special precautions for user

Special Provisions 274, 335, 966, 967, 969
Limited Quantity (LQ) 5 kg
EmS-No. F-A, S-F

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN3077
14.2 UN proper shipping name Environmentally hazardous substances, solid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes (coated with aliphatic acid))
14.3 Transport hazard class(es) 9
14.4 Packing group III
Description UN3077, Environmentally hazardous substances, solid, n.o.s. (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Copper flakes (coated with aliphatic acid)), 9, III
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions A97, A158, A179, A197, A215
Limited quantity (LQ) 30 kg G
ERG Code 9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 09-Jul-2024

Indication of changes

Revision note SDS sections updated, 2, 3, 4, 8.
Training Advice When working with hazardous materials, regular training of operators is required by law
Further information No information available

SAFETY DATA SHEET

EVO-STIK PLUMBER'S MAIT QUICK LEAK REPAIR PUTTY
Supersedes date 31-Mar-2023

Revision date 09-Jul-2024
Revision Number 2.02

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet