



# SAFETY DATA SHEET

DOW CHEMICAL COMPANY LIMITED

Safety Data Sheet according to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

**Product name:** DOWSIL™ SE 4420 RTV Sealant

**Revision Date:** 14.07.2023

**Version:** 5.0

**Date of last issue:** 08.11.2022

**Print Date:** 15.07.2023

DOW CHEMICAL COMPANY LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

**Product name:** DOWSIL™ SE 4420 RTV Sealant

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Use at industrial sites: Manufacture of computer, electronic and optical products, electrical equipment. Use in adhesives.

### 1.3 Details of the supplier of the safety data sheet

#### **COMPANY IDENTIFICATION**

DOW CHEMICAL COMPANY LIMITED  
5 OAKWATER AVENUE  
CHEADLE ROYAL BUSINESS PARK  
CHEADLE  
SK8 3SR  
UNITED KINGDOM

**Customer Information Number:**

+44 (0) 1663 746518

SDSQuestion@dow.com

**Fax:**

+44 (0) 1663 746605

### 1.4 EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 0031 115 694 982

**Local Emergency Contact:** 00 31 115 69 4982

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008, as retained and amended in UK law**

Flammable liquids - Category 3 - H226

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008, as retained and amended in UK law

### Hazard pictograms



Signal word: **WARNING**

### Hazard statements

H226 Flammable liquid and vapour.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P233 Keep container tightly closed.

P303 + P361 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents and/or container to an approved waste disposal plant.

## 2.3 Other hazards

This product contains no substances assessed to be PBT or vPvB at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone

### 3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	UK REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008, as retained and amended in UK law
CASRN 68909-20-6 EC-No. 272-697-1 Index-No. 014-052-00-7	—	>= 1.7 - <= 1.8 %	silanamine, 1,1,1- trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	STOT RE 2; H373 (Lungs) EUH066

				Acute toxicity estimate Acute oral toxicity: > 2,000 mg/kg Acute dermal toxicity: > 2,000 mg/kg
--	--	--	--	---

Substances with a workplace exposure limit

<b>CASRN</b> 1344-28-1 <b>EC-No.</b> 215-691-6 <b>Index-No.</b> —	—	>= 71.0 - <= 74.0 %	Aluminum oxide	Not classified  Acute toxicity estimate Acute oral toxicity: > 5,000 mg/kg Acute inhalation toxicity: > 2.3 mg/l, dust/mist
--	---	---------------------	----------------	---

<b>CASRN</b> 1185-55-3 <b>EC-No.</b> 214-685-0 <b>Index-No.</b> —	—	>= 1.9 - <= 2.0 %	Methyltrimethoxysilane	Flam. Liq. 2; H225  Acute toxicity estimate Acute oral toxicity: 11,685 mg/kg Acute inhalation toxicity: > 7605 ppm, 6 Hour, vapour Acute dermal toxicity: > 9,500 mg/kg
--	---	-------------------	------------------------	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

#### General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air and keep comfortable for breathing; consult a physician.

**Skin contact:** Wash off with plenty of water.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** Rinse mouth with water. No emergency medical treatment necessary.

### 4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

## **SECTION 5: FIREFIGHTING MEASURES**

---

### **5.1 Extinguishing media**

**Suitable extinguishing media:** Alcohol-resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Dry sand.

**Unsuitable extinguishing media:** High volume water jet. Do not use direct water stream..

### **5.2 Special hazards arising from the substance or mixture**

**Hazardous combustion products:** Silicon oxides. Formaldehyde. Carbon oxides.

**Unusual Fire and Explosion Hazards:** Flash back possible over considerable distance.. Exposure to combustion products may be a hazard to health.. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.. Flammable mixtures may exist within the vapor space of containers at room temperature.. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat.. Vapours may form explosive mixtures with air..

### **5.3 Advice for firefighters**

**Fire Fighting Procedures:** Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed.. Do not use a solid water stream as it may scatter and spread fire..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

---

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Ground and bond all containers and handling equipment. Vapor explosion hazard. Keep out of sewers. Follow safe handling advice and personal protective equipment recommendations.

**6.2 Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**6.3 Methods and materials for containment and cleaning up:** Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

**6.4 Reference to other sections:**

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: HANDLING AND STORAGE

---

**7.1 Precautions for safe handling:** Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ground and bond container and receiving equipment.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

**7.3 Specific end use(s):** See the technical data sheet on this product for further information.

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Aluminum oxide	ACGIH	TWA Respirable particulate matter	1 mg/m3 , Aluminium
	Further information: A4: Not classifiable as a human carcinogen		
	GB EH40	TWA inhalable dust	10 mg/m3
	GB EH40	TWA Respirable dust	4 mg/m3
Methyltrimethoxysilane	Dow IHG	TWA	7.5 ppm

methanol	ACGIH	TWA	200 ppm
	Further information: Skin: Danger of cutaneous absorption		
	ACGIH	STEL	250 ppm
	Further information: Skin: Danger of cutaneous absorption		
	GB EH40	TWA	266 mg/m3 200 ppm
	Further information: Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
	GB EH40	STEL	333 mg/m3 250 ppm
	Further information: Sk: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:

Methanol.

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

#### Recommended monitoring procedures

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with the Occupational Exposure Limits and the adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples should be analysed by an accredited laboratory.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy); European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents); European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods. Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods. Health and Safety Executive (HSE), United Kingdom: Methods for the Determination of Hazardous Substances.

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany.

L'Institut National de Recherche et de Sécurité, (INRS), France.

**Derived No Effect Level**

Aluminum oxide

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	3.0 mg/m3	n.a.	3.0 mg/m3

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	0.750 mg/m3	n.a.	n.a.	0.750 mg/m3

Methyltrimethoxysilane

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	3.6 mg/m3	25.6 mg/m3	n.a.	n.a.

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	7.2 mg/m3	6.25 mg/m3	0.26 mg/m3	n.a.	n.a.

**Predicted No Effect Concentration**

Aluminum oxide

Compartment	PNEC
Sewage treatment plant	20 mg/l

Methyltrimethoxysilane

Compartment	PNEC
Fresh water sediment	0.73 mg/kg
Marine sediment	0.073 mg/kg
Soil	0.03 mg/kg

**8.2 Exposure controls**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

**Individual protection measures**

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

**Skin protection**

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Wear clean, body-covering clothing.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	viscous liquid
Color	white
Odor	slight
Odor Threshold	No data available
pH	Not applicable, substance/mixture is non-soluble (in water)
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 100 °C
Flash point	<b>Seta closed cup</b> 43 °C
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable



Flammability (liquids)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	2.25
Water solubility	insoluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	80,000 mPa.s
Kinematic Viscosity	No data available
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

#### 9.2 Other information

Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## SECTION 10: STABILITY AND REACTIVITY

---

**10.1 Reactivity:** Not classified as a reactivity hazard.

**10.2 Chemical stability:** Stable under normal conditions.

**10.3 Possibility of hazardous reactions:** Can react with strong oxidizing agents. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. Vapours may form explosive mixture with air. Flammable liquid and vapour.

**10.4 Conditions to avoid:** Avoid static discharge. Heat, flames and sparks.

**10.5 Incompatible materials:** Avoid contact with oxidizing materials.

**10.6 Hazardous decomposition products:**

Decomposition products can include and are not limited to: Methanol. Formaldehyde.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data are available.*

### 11.1 Information on toxicological effects

**Information on likely routes of exposure**

Inhalation, Eye contact, Skin contact, Ingestion.

**Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)**

**Acute Toxicity Endpoints:**

**Acute oral toxicity**

**Information for the Product:**

Very low toxicity if swallowed. Signs and symptoms of excessive exposure may include: Gastrointestinal irritation.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):  
LD50, Rat, > 5,000 mg/kg Estimated.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on testing for product(s) in this family of materials: LD50, Rat, > 2,000 mg/kg  
OECD 401 or equivalent No deaths occurred at this concentration.

**Aluminum oxide**

LD50, Rat, > 5,000 mg/kg OECD Test Guideline 401

**Methyltrimethoxysilane**

LD50, Rat, male and female, 11,685 mg/kg

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

**Acute dermal toxicity**

**Information for the Product:**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

The dermal LD50 has not been determined.

For similar material(s): LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

**Aluminum oxide**

The dermal LD50 has not been determined.

**Methyltrimethoxysilane**

LD50, Rabbit, male and female, > 9,500 mg/kg OECD 402 or equivalent

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

**Acute inhalation toxicity****Information for the Product:**

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

**Information for components:****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

The LC50 has not been determined.

**Aluminum oxide**

LC50, Rat, male and female, dust/mist, > 2.3 mg/l No deaths occurred at this concentration.

**Methyltrimethoxysilane**

LC50, Rat, male and female, 6 Hour, vapour, > 7605 ppm OECD Test Guideline 403

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

**Skin corrosion/irritation****Information for the Product:**

Based on information for component(s):  
Brief contact is essentially nonirritating to skin.

**Information for components:****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on testing for product(s) in this family of materials:  
Brief contact is essentially nonirritating to skin.  
Repeated exposure may cause skin dryness or cracking.

**Aluminum oxide**

Brief contact is essentially nonirritating to skin.  
Mechanical injury only.

**Methyltrimethoxysilane**

Brief contact may cause slight skin irritation with local redness.

**Serious eye damage/eye irritation**

**Information for the Product:**

Based on information for component(s):  
May cause slight temporary eye irritation.  
Corneal injury is unlikely.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on testing for product(s) in this family of materials:  
May cause irritation or corneal injury due to mechanical action.

**Aluminum oxide**

Solid or dust may cause irritation or corneal injury due to mechanical action.

**Methyltrimethoxysilane**

May cause slight temporary eye irritation.  
Corneal injury is unlikely.

**Sensitization**

**Information for the Product:**

For skin sensitization:  
Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

For skin sensitization:  
Based on testing for product(s) in this family of materials:  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Aluminum oxide**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Methyltrimethoxysilane**

For skin sensitization:  
Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

**Information for the Product:**

Product test data not available.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Aluminum oxide**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Methyltrimethoxysilane**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Aspiration Hazard**

**Information for the Product:**

Based on physical properties, not likely to be an aspiration hazard.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on physical properties, not likely to be an aspiration hazard.

**Aluminum oxide**

Based on physical properties, not likely to be an aspiration hazard.

**Methyltrimethoxysilane**

Material is not classified as an aspiration hazard based on insufficient data, however materials with low viscosity may be aspirated into the lungs during ingestion or vomiting.

**Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)**

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

**Information for the Product:**

Product test data not available.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

In animals, effects have been reported on the following organs:

lung

Due to the physical state of the material, this component is not expected to be bioavailable under normal handling and processing conditions.

**Aluminum oxide**

Repeated excessive exposures to alumina (aluminium oxide) dust or fumes may cause respiratory effects.

Exposure to alumina alone has not been shown to cause chronic lung disease. Some forms of alumina, when injected directly into the lungs of animals, caused fibrosis, but this is an abnormal route of exposure.

**Methyltrimethoxysilane**

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

**Carcinogenicity**

**Information for the Product:**

Product test data not available.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

No relevant data found.

**Aluminum oxide**

Although certain forms of alumina have been reported to induce tumors when injected directly into the lungs of laboratory animals, there is no evidence that alumina is carcinogenic under normal routes of exposure.

**Methyltrimethoxysilane**

No relevant data found.

**Teratogenicity**

**Information for the Product:**

Product test data not available.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on testing for product(s) in this family of materials: Did not cause birth defects or any other fetal effects in laboratory animals.

**Aluminum oxide**

High doses of aluminium and aluminium salts given to laboratory animals during pregnancy have caused developmental toxicity in the fetus at doses mildly toxic to the mother. The relevance of these data to alumina is unknown.

**Methyltrimethoxysilane**

Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

**Information for the Product:**

Product test data not available.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on testing for product(s) in this family of materials: In animal studies, did not interfere with reproduction.

**Aluminum oxide**

No relevant data found.

**Methyltrimethoxysilane**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

**Information for the Product:**

Product test data not available.

**Information for components:**

**silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

Based on testing for product(s) in this family of materials: In vitro genetic toxicity studies were negative.

**Aluminum oxide**

For similar material(s): In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were predominantly negative.

**Methyltrimethoxysilane**

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

*Ecotoxicological information appears in this section when such data are available.*

## 12.1 Toxicity

### **silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

#### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on testing for product(s) in this family of materials:

LC50, Danio rerio (zebra fish), 96 Hour, > 1,000 mg/l, OECD Test Guideline 203

#### **Acute toxicity to aquatic invertebrates**

Based on testing for product(s) in this family of materials:

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

#### **Acute toxicity to algae/aquatic plants**

ErC50, Scenedesmus quadricauda (Green algae), 72 Hour, > 10,000 mg/l, OECD Test Guideline 201

#### **Toxicity to bacteria**

Based on testing for product(s) in this family of materials:

EC50, activated sludge, 3 Hour, Respiration rates., > 1,000 mg/l, OECD Test Guideline 209

### **Aluminum oxide**

#### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

EC50, Fish, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

#### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

#### **Acute toxicity to algae/aquatic plants**

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 100 mg/l, OECD Test Guideline 201 or Equivalent

#### **Chronic toxicity to fish**

NOEC, Pimephales promelas (fathead minnow), 7 d, 7.1 mg/l

#### **Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 28 d, 1.89 mg/l

### **Methyltrimethoxysilane**

#### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, > 110 mg/l, OECD Test Guideline 203 or Equivalent

#### **Acute toxicity to aquatic invertebrates**



EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 122 mg/l, OECD Test Guideline 202

**Acute toxicity to algae/aquatic plants**

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate inhibition, > 3.6 mg/l, OECD Test Guideline 201

No toxicity at the limit of solubility

NOEC, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate inhibition, >= 3.6 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

EC10, activated sludge, Static, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, >= 10 mg/l

**12.2 Persistence and degradability****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

**Biodegradability:** Biodegradation is not applicable.

**Aluminum oxide**

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

**Methyltrimethoxysilane**

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

**Biodegradation:** 54 %

**Exposure time:** 28 d

**Method:** Regulation (EC) No. 440/2008, Annex, C.4-A

**12.3 Bioaccumulative potential****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

**Bioaccumulation:** No relevant data found.

**Aluminum oxide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**Methyltrimethoxysilane**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** -0.82 Estimated.

**12.4 Mobility in soil****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

No relevant data found.

**Aluminum oxide**

No relevant data found.

**Methyltrimethoxysilane**

No relevant data found.

**12.5 Results of PBT and vPvB assessment****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**Aluminum oxide**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**Methyltrimethoxysilane**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**12.6 Other adverse effects****silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Aluminum oxide**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Methyltrimethoxysilane**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to ECDirective 2008/98/EC, provided it fulfils the criteria listed in Annex III of this directive. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**Classification for ROAD and Rail transport (ADR/RID):**

**14.1 UN number or ID number** UN 1993

**14.2 UN proper shipping name** FLAMMABLE LIQUID, N.O.S.(Methyltrimethoxysilane)

- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not considered environmentally hazardous based on available data.

- 14.6 Special precautions for user  
Hazard Identification Number: 30

**Classification for INLAND waterways (ADNR/ADN):**  
**Consult your Dow contact before transporting by inland waterway**

**Classification for SEA transport (IMO-IMDG):**

- 14.1 UN number or ID number UN 1993
- 14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S.(Methyltrimethoxysilane)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not considered as marine pollutant based on available data.
- 14.6 Special precautions for user EmS: F-E, S-E
- 14.7 Maritime transport in bulk  
according to IMO instruments Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

- 14.1 UN number or ID number UN 1993
- 14.2 UN proper shipping name Flammable liquid, n.o.s.(Methyltrimethoxysilane)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not applicable
- 14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## SECTION 15: REGULATORY INFORMATION

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### UK REACH - UK Statutory Instruments 2019 No.758 as amended

This product contains only components that have been either registered, notified for downstream user import (DUIN), are exempt from registration, are regarded as registered or are not subject to registration according to UK Statutory Instruments 2019 No.758 as amended (UK REACH)., Polymers are exempted from registration under REACH. All relevant starting materials and additives have been registered, notified for downstream user import (DUIN) or are exempt from registration according to UK Statutory Instruments 2019 No.758 as amended (UK REACH)., The aforementioned indications of the UK REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, expressed or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

#### UK REACH List of restrictions (Annex 17)

Conditions of restriction for the following entries should be considered:  
Number on list 3

#### Control of Major Accident Hazards Regulations 2015 (COMAH)

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5,000 t

50,000 t

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

---

## SECTION 16: OTHER INFORMATION

---

#### Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Flam. Liq. - 3 - H226 - Based on product data or assessment

#### Revision

Identification Number: 4026232 / A279 / Issue Date: 14.07.2023 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
Dow IHG	Dow Industrial Hygiene Guideline
GB EH40	UK. EH40 WEL - Workplace Exposure Limits
STEL	Short-term exposure limit
TWA	Time weighted average
Flam. Liq.	Flammable liquids
STOT RE	Specific target organ toxicity - repeated exposure

**Full text of other abbreviations**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL COMPANY LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to

change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

GB