
# **PTC Thermistor**





# RoHS Compliant

# **Description**

This type series are characterized by a temperature curve showing a positive temperature coefficient. Available standard executions are shrink-sleeve or PPS housing package, beside these there are manifold customized solutions on hand.

## **Applications**

- · Household appliances
- · Electronics
- Engineering
- · Automotive


#### **Features**

- Temperatures from -40°C up to +170°C
- Excellent long-temperature stability
- · High precision and reliability
- No reversal polarity (+/-) possible

# **Technical data**

| Ratings                                | Туре                  |  |  |  |  |  |
|--|-----------------------|--|--|--|--|--|
| Typical resistance at 100°C (±3%)      | 1000Ω                 |  |  |  |  |  |
| Operating temperature range            | -40°C to +170 (190)°C |  |  |  |  |  |
| Minimum insulation resistance (100VDC) | 100ΜΩ                 |  |  |  |  |  |
| Operating current                      | 1 mA                  |  |  |  |  |  |
| Maximum rated power                    | 10 mW                 |  |  |  |  |  |

## Standard types



Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro




# **PTC Thermistor**



### Temperature vs. Resistance

| T°C  | -10 | 0   | 10  | 20  | 30  | 40  | 50  | 60  | 70  | 80  | 90  | 100  | 110  | 120  | 130  | 140  | 150  | 160  | 170  |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|
| min. | 414 | 452 | 493 | 537 | 582 | 629 | 678 | 733 | 788 | 846 | 907 | 970  | 1030 | 1094 | 1162 | 1227 | 1290 | 1346 | 1396 |
| typ. | 435 | 475 | 517 | 562 | 608 | 656 | 706 | 761 | 817 | 875 | 937 | 1000 | 1064 | 1132 | 1204 | 1274 | 1341 | 1402 | 1457 |
| max. | 456 | 498 | 541 | 587 | 634 | 683 | 734 | 789 | 846 | 904 | 967 | 1030 | 1098 | 1170 | 1246 | 1321 | 1392 | 1458 | 1518 |



#### **Part Number Table**

| Description   | Part Number |  |  |  |
|---|-------------|--|--|--|
| PTC Thermistor, Cylindrical Housing, STS1, 1KΩ, 0.3%, G918            | MP015805    |  |  |  |
| PTC Thermistor, Shrink Sleeve Housing, STS1, 1K $\Omega$ , 0.3%, U129 | MP015806    |  |  |  |

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

