


Automotive-grade ACEPACK DMT-32 power module, sixpack topology, 1200 V, 47.5 mΩ typ. SiC Power MOSFET with NTC



Features

- AQC 324 qualified
- 1200 V blocking voltage
- 47.5 mΩ of typical $R_{DS(on)}$
- Maximum operating junction temperature $T_J = 175\text{ }^{\circ}\text{C}$
- DBC Cu-AlN-Cu based substrate to improve thermal performance
- Isolation voltage 3 kV
- Integrated NTC temperature sensor
- Zig-zag pin-out


Applications

- On board charger (OBC)

Description

This ACEPACK DMT-32 power module realizes a sixpack topology with integrated NTC, tailored for the DC/DC converter stage of the OBC in hybrid and electric vehicles. The power module features six silicon carbide Power MOSFETs of 2nd generation from STMicroelectronics. Thanks to the well-recognized chip technology, the ACEPACK DMT-32 ensures the best compromise between energy losses and high switching frequency operation mode. This module allows you to create complex topologies with very high power densities as well as high efficiency requirements. The AlN insulated substrate enables optimal thermal performance. Moreover, thanks to the specific design featuring grooves on the molding ensure a high creepage distance.

The zig-zag pin option improves the flexibility at PCB level.



Product status link

[M2P45M12W2-1LA](#)

Product summary

Order code	M2P45M12W2-1LA
Marking	M2P45M12W2-1LA
Package	ACEPACK DMT-32 zig-zag
Packing	Tube

1 Inverter switch

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source breakdown voltage	1200	V
V_{GS}	Gate-source voltage	-10 to 22	V
	Gate-source voltage (recommended operating values)	-5 to 18	
I_D	Drain current (continuous) at $T_C = 50\text{ °C}$	30	A
$I_{DM}^{(1)}$	Drain current (pulsed, $t_p = 1\text{ ms}$)	95	A
T_J	Operating junction temperature range	-40 to 175	°C

1. Pulse width is limited by safe operating area.

Table 2. Electrical characteristics - SiC MOSFET

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	1200			V
$R_{DS(on)}$	Static drain-source on resistance	$V_{GS} = 18\text{ V}, I_D = 20\text{ A}$		47.5	60.5	mΩ
		$V_{GS} = 18\text{ V}, I_D = 20\text{ A}, T_J = 175\text{ °C}$		101		
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 1\text{ mA}$	1.9	3.1	5	V
I_{DSS}	Zero gate voltage drain current	$V_{GS} = 0\text{ V}, V_{DS} = 1200\text{ V}$			10	μA
I_{GSS}	Gate-body leakage current	$V_{DS} = 0\text{ V}, V_{GS} = -10\text{ to }22\text{ V}$			±100	nA
C_{iss}	Input capacitance	$V_{DS} = 800\text{ V}, f = 1\text{ MHz}, V_{GS} = 0\text{ V}$		2086		pF
C_{oss}	Output capacitance			90		pF
C_{rss}	Reverse transfer capacitance			18		pF
R_G	Intrinsic gate resistance	$f = 1\text{ MHz}$ open drain		1		Ω
Q_g	Total gate charge	$V_{DD} = 800\text{ V}, I_D = 25\text{ A},$ $V_{GS} = -5\text{ to }18\text{ V}$		100		nC
Q_{gs}	Gate-source charge			22.4		nC
Q_{gd}	Gate-drain charge			60.7		nC
E_{on}	Turn-on switching energy	$V_{DS} = 800\text{ V}, I_D = 25\text{ A}, V_{GS} = -5\text{ to }18\text{ V},$ $R_{G(on)} = 15\text{ Ω}, R_{G(off)} = 2.2\text{ Ω}$		518		μJ
E_{off}	Turn-off switching energy			86		μJ
E_{on}	Turn-on switching energy	$V_{DS} = 800\text{ V}, I_D = 25\text{ A}, V_{GS} = -5\text{ to }18\text{ V},$ $R_{G(on)} = 15\text{ Ω}, R_{G(off)} = 2.2\text{ Ω}, T_J = 175\text{ °C}$		675		μJ
E_{off}	Turn-off switching energy			81		μJ
R_{thJC}	Thermal resistance, junction-to-case			0.38		°C/W

Table 3. Reverse intrinsic SiC diode characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{SD}	Forward on voltage drop	$V_{GS} = 0\text{ V}$, $I_{SD} = 20\text{ A}$	-	2.5	-	V
t_{rr}	Reverse recovery time	$I_{SD} = 25\text{ A}$, $V_{DD} = 800\text{ V}$, $di/dt_{on} = 2000\text{ A}/\mu\text{s}$, $V_{GS} = -5\text{ to }18\text{ V}$, $R_G = 12\ \Omega$	-	13.5	-	ns
Q_{rr}	Reverse recovery charge		-	189	-	nC
I_{RRM}	Reverse recovery current		-	24.4	-	A
t_{rr}	Reverse recovery time		-	31	-	ns
Q_{rr}	Reverse recovery charge	$I_{SD} = 25\text{ A}$, $V_{DD} = 800\text{ V}$, $di/dt_{on} = 2000\text{ A}/\mu\text{s}$, $V_{GS} = -5\text{ to }18\text{ V}$, $R_G = 12\ \Omega$, $T_J = 175\text{ }^\circ\text{C}$	-	574	-	nC
I_{RRM}	Reverse recovery current		-	32	-	A


2 NTC

Table 4. Absolute maximum ratings for NTC temperature sensor, considered as stand-alone

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
R_{25}	Resistance rating	$T = 25\text{ }^{\circ}\text{C}$		10		$\text{k}\Omega$
$\Delta R_{25}/R$	Resistance tolerance		-2		+2	%
R_{100}	Resistance rating	$T = 100\text{ }^{\circ}\text{C}$		674.8		Ω
$\Delta R_{100}/R$	Resistance tolerance		-4.75		4.75	%
$R_{25/50}$	B-value	$T = 25\text{ }^{\circ}\text{C}$ to $50\text{ }^{\circ}\text{C}$		3940		K
$R_{25/85}$		$T = 25\text{ }^{\circ}\text{C}$ to $85\text{ }^{\circ}\text{C}$		3980		
$R_{25/100}$		$T = 25\text{ }^{\circ}\text{C}$ to $100\text{ }^{\circ}\text{C}$ ($\pm 1\%$)		4000		
T	Operating temperature range		-40		150	$^{\circ}\text{C}$

3 Electrical topology and pin description

Figure 1. ACEPACK DMT-32 zig-zag pin layout (bottom view)




DM00692330_ZigZag_rev_6_pin_layout

Table 5. Pin description

Pin	Description	Pin	Description
1	N	17	P
2	N	18	P
3	NC	19	G1
4	NC	20	S1
5	PH3	21	G2
6	PH3	22	S2
7	NC	23	G3
8	NC	24	S3
9	PH2	25	G4
10	PH2	26	S4
11	NC	27	G5
12	NC	28	S5
13	PH1	29	G6
14	PH1	30	S6
15	T2 (NTC)	31	NC
16	T1 (NTC)	32	NC

Figure 2. Electrical topology and pin description



4 Electrical characteristics (curves)

Figure 3. Typical output characteristics ($T_J = -40\text{ }^{\circ}\text{C}$)




Figure 4. Typical output characteristics ($T_J = 25\text{ }^{\circ}\text{C}$)




Figure 5. Typical output characteristics ($T_J = 175\text{ }^{\circ}\text{C}$)




Figure 6. Typical transfer characteristics




Figure 7. Typical reverse conduction characteristics ($T_J = -40\text{ }^{\circ}\text{C}$)




Figure 8. Typical reverse conduction characteristics ($T_J = 25\text{ }^{\circ}\text{C}$)




Figure 9. Typical reverse conduction characteristics
($T_J = 175^\circ\text{C}$)




Figure 10. Typical switching energy vs temperature




Figure 11. Typical switching energy vs drain current
($T_J = 25^\circ\text{C}$)




Figure 12. Typical switching energy vs drain current
($T_J = 175^\circ\text{C}$)




Figure 13. Typical switching energy vs gate resistance
($T_J = 25^\circ\text{C}$)




Figure 14. Typical switching energy vs gate resistance
($T_J = 175^\circ\text{C}$)




Figure 15. Typical switching energy vs bus voltage
($T_J = 25^\circ\text{C}$)




Figure 16. Typical switching energy vs bus voltage
($T_J = 175^\circ\text{C}$)




Figure 17. Typical gate charge characteristics





Figure 18. Typical transient thermal impedance



5 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

5.1 ACEPACK DMT-32 zig-zag package information

Figure 19. ACEPACK DMT-32 zig-zag package outline




Table 6. ACEPACK DMT-32 zig-zag package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	43.50	44.00	44.50
A1	38.80	39.00	39.20
B	26.90	27.40	27.90
B1	15.90	16.05	16.20
B2	18.80	18.95	19.10
C	5.50	5.70	5.90
C1	3.15	3.30	3.45
C2	8.90	9.40	9.90
e	3.50	3.70	3.90
e1	1.60	1.80	2.00
D	33.00	33.40	33.80
E	15.10	15.50	15.90
f	0.60	0.65	0.70
R	1.60		1.70
T	0.48	0.53	0.58
V	90°		93°
aaa		0.30	
bbb		0.15	

Table 7. Ratings for module

Symbol	Parameter	Value	Unit
V _{ISO}	Isolation voltage (f = 50 Hz, t = 60 s)	3	kV
CTI	Comparative tracking index	600	V
T _{stg}	Storage temperature range	-40 to 150	°C

Revision history

Table 8. Document revision history

Date	Revision	Changes
23-Nov-2023	1	First release.
16-Dec-2024	2	Minor text changes in Section Features and Section Description .

Contents

1	Inverter switch.....	2
2	NTC	4
3	Electrical topology and pin description	5
4	Electrical characteristics (curves).....	7
5	Package information.....	10
5.1	ACEPACK DMT-32 zig-zag package information	10
	Revision history	12

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved