



Color: ■ dark gray



## Electrical data

### Ratings per IEC/EN

Nominal voltage (III/3)	400 V
Rated current	41 A

## Physical data

Width	12.3 mm / 0.484 inches
Height	3.8 mm / 0.15 inches
Depth	23.9 mm / 0.941 inches
Jumper assignment	1-2

**Material data**

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Color	dark gray
Insulation material (main housing)	Polyamide (PA66)
Fire load	0 MJ
Weight of insulation material	0.28 g
Weight	2.7 g

**Environmental requirements**

Continuous operating temperature	-60 ... +105 °C
----------------------------------	-----------------

**Commercial data**

PU (SPU)	5 pcs
Packaging type	Bag
Country of origin	CN
GTIN	4055144067965
Customs tariff number	85366990990

**Product classification**

UNSPSC	39121421
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Downloads****Environmental Product Compliance**

## Compliance Search

Environmental Product Compliance 221-942	
------------------------------------------	-------------------------------------------------------------------------------------

**Documentation**

## Bid Text

221-942	docx 27.51 KB	
221-942	xml 2.96 KB	

## CAD/CAE-Data

### CAD data

2D/3D Models 221-942



## Installation Notes

### Commoning



Extending the N and PE (ground) distribution via jumper

### Commoning



Insert the jumper without a locking function into open clamping units.

### Commoning



Without a locking function:  
The jumper without a locking function is plugged into the splicing connectors.

### Commoning



Remove the jumper from open clamping units.