


## 40V, 0.75A Schottky Barrier Diode

### Product Summary

| Parameter                               | Rating          |
|-----------------------------------------|-----------------|
| $V_{RRM}$                               | 40 V            |
| $V_F \text{ Max @ } 750\text{mA}$       | 740 mV          |
| $I_{F(AV)}$                             | 750 mA          |
| $I_R \text{ Max @ } V_F = 40 \text{ V}$ | 8 $\mu\text{A}$ |



### Features


- Extremely Low Thermal Resistance
- For Surface Mount Application And High Current Capability

### SOD-323

### Mechanical Data

- Package: SOD-323
- Moisture Sensitivity: Level 1, per J-STD-020
- Halogen Free. "Green" Device (Note1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish & RoHS Compliant
- Weight: 0.004 g (approximate)

### Body Marking and Pin Layout

| Body Marking                                                                                                                                                                                                                                                                                                      | Internal structure                                                                                                 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
|  <p>XX: Device Marking Code<sup>1</sup><br/> <b>Bar</b>: Cathode Pin indicator<br/> <b>Dot</b>(optional): Manufacturing Site Marking</p> <p><sup>1</sup>   Refer to the ordering information for the specific device code.</p> |  <p>1 Cathode      2 Anode</p> |

### Ordering Information

| Ordering Product Name | Device Marking Code | Reel Size | Packing Type | Qty/Reel |
|-----------------------|---------------------|-----------|--------------|----------|
| Product Name-TP       | 2G                  | 7"        | Tape & Reel  | 3,000    |
| Product Name-13P      | 2G                  | 13"       | Tape & Reel  | 10,000   |

For packaging details, visit our website at <https://www.mccsemi.com/Package/List>

**40V, 0.75A Schottky Barrier Diode**

**Maximum Ratings ( $T_A=25^\circ\text{C}$  unless otherwise specified)**

| Parameter                             |                                                           | Symbol       | Rating      | Unit             |
|---------------------------------------|-----------------------------------------------------------|--------------|-------------|------------------|
| Peak Repetitive Reverse Voltage       |                                                           | $V_{RRM}$    | 40          | V                |
| RMS Reverse Voltage                   |                                                           | $V_{R(RMS)}$ | 28          | V                |
| Reverse Voltage                       |                                                           | $V_R$        | 40          | V                |
| Average Forward Current               |                                                           | $I_{F(AV)}$  | 750         | mA               |
| Non-Repetitive Peak Surge Current     | $t_p=8.3\text{ms}$ Half Sine Wave, $T_J=25^\circ\text{C}$ | $I_{FSM}$    | 10          | A                |
| Power Dissipation <sup>(Note 2)</sup> |                                                           | $P_D$        | 380         | mW               |
| Operating Junction Temperature Range  |                                                           | $T_J$        | -55 to +150 | $^\circ\text{C}$ |
| Storage Temperature Range             |                                                           | $T_{STG}$    | -55 to +150 | $^\circ\text{C}$ |

Notes:  
1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.  
2. Device mounted on an FR4 Printed-Circuit Board (PCB) with the recommended pad layout.

**Thermal characteristics ( $T_A=25^\circ\text{C}$  unless otherwise specified)**


| Parameter                                                       | Symbol          | Rating | Unit               |
|-----------------------------------------------------------------|-----------------|--------|--------------------|
| Thermal Resistance from Junction to Ambient <sup>(Note 2)</sup> | $R_{\theta JA}$ | 330    | $^\circ\text{C/W}$ |

**Electrical Characteristics ( $T_A=25^\circ\text{C}$  unless otherwise specified)**


| Parameter                 | Test Conditions                                                          | Symbol   | Min | Typ  | Max  | Unit          |
|---------------------------|--------------------------------------------------------------------------|----------|-----|------|------|---------------|
| Reverse Breakdown Voltage | $I_R=1\text{ mA}$ (pulse test)                                           | $V_{BR}$ | 40  |      |      | V             |
| Forward Voltage           | $I_F=10\text{ mA}$                                                       | $V_F$    |     | 0.29 | 0.38 | V             |
|                           | $I_F=100\text{ mA}$                                                      |          |     | 0.37 | 0.47 |               |
|                           | $I_F=250\text{ mA}$                                                      |          |     | 0.42 | 0.54 |               |
|                           | $I_F=500\text{ mA}$                                                      |          |     | 0.48 | 0.64 |               |
|                           | $I_F=750\text{ mA}$                                                      |          |     | 0.54 | 0.74 |               |
| Reverse Current           | $V_R=30\text{ V}$                                                        | $I_R$    |     | 1.2  |      | $\mu\text{A}$ |
|                           | $V_R=40\text{ V}$                                                        |          |     | 2    | 8    |               |
|                           | $V_R=40\text{ V}, T_J=125^\circ\text{C}$                                 |          |     | 1.5  |      | mA            |
| Junction Capacitance      | $V_R=10\text{ V}, f=1.0\text{MHz}$                                       | $C_J$    |     | 15   |      | pF            |
| Reverse Recovery Time     | $I_F=10\text{mA}, I_R=10\text{mA}, I_{rr}=0.1 \times I_R, R_L=100\Omega$ | $t_{rr}$ |     |      | 20   | ns            |

## Curve Characteristics


**Fig.1 - Typical Instantaneous Forward Characteristics (per diode)**




**Fig.2 - Typical Reverse Leakage Characteristics (per diode)**




**Fig.3 - Typical Capacitance Characteristics (per diode)**



**Fig.4 - Power Derating Curve**



## Package Outline




| DIM | INCH  |       | MM   |       | NOTE   |
|-----|-------|-------|------|-------|--------|
|     | MIN   | MAX   | MIN  | MAX   |        |
| A   | 0.031 | 0.045 | 0.80 | 1.15* | Note 1 |
| A1  | 0.000 | 0.006 | 0.00 | 0.15  |        |
| b   | 0.010 | 0.016 | 0.25 | 0.40  |        |
| c   | 0.003 | 0.010 | 0.08 | 0.25  |        |
| D   | 0.090 | 0.107 | 2.30 | 2.70  |        |
| D1  | 0.063 | 0.071 | 1.60 | 1.80  |        |
| E   | 0.045 | 0.055 | 1.15 | 1.40  |        |
| L1  | 0.004 | 0.018 | 0.10 | 0.45  |        |

**Notes:**

1. Dimension A for products from manufacturing site VN is controlled at max 1.10 mm.

## Suggested Pad Layout (Unit:mm)



**Notes:**

1. The suggested land pattern dimensions have been provided for reference only.
2. For further information, please refer to document IPC-7351A.

## DISCLAIMERS

Micro Commercial Components Corp. (MCC) reserves the right to make changes to any product without prior notice, including corrections, modifications, enhancements, improvements, or other changes. MCC's products are not designed, authorized, or warranted for use in medical, military, aircraft, space, or life support equipment, nor in applications where failure or malfunction of an MCC product can reasonably be expected to result in personal injury, death, or severe property or environmental damage. MCC does not assume liability for any application or use of the products described herein, nor does it convey any license under its patent rights or those of others. Users of MCC's products in any such application assume all risks associated with their use and agree to hold MCC and all companies whose products are represented on our website harmless against any damages. MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of MCC.

Counterfeiting of semiconductor parts is an increasing problem in the industry. MCC is taking strong measures to protect both ourselves and our customers from counterfeit products. We strongly encourage customers to purchase our parts either directly from MCC or through Authorized Distributors, who are listed by country on our website. Products purchased directly from MCC or from Authorized Distributors are genuine, have full traceability, and meet our quality standards for handling and storage. MCC will not provide warranty coverage or any other assistance for parts bought from Unauthorized Sources.

This document, along with the item(s) described within, may be subject to export control regulations. Exporting these items may require prior authorization from national authorities.

**Terms and Conditions** - MCC products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.