



Product Change Notification: SYST-24EAAV013

Date:

30-Mar-2026

Product Category:

Clock And Timing - Oscillators

Notification Subject:

Data Sheet - DSC12x2/3/4 - High Performance Differential MEMS Oscillators

Affected CPNs:

[SYST-24EAAV013_Affected_CPN_03302026.pdf](#)

[SYST-24EAAV013_Affected_CPN_03302026.csv](#)

Notification Text:

SYST-24EAAV013

Microchip has released a new Datasheet for the DSC12x2/3/4 - High Performance Differential MEMS Oscillators of devices. If you are using one of these devices please read the document located at [DSC12x2/3/4 - High Performance Differential MEMS Oscillators](#).

Notification Status: Final

Description of Change:

- Added a note regarding bulk quantities to the Product Identification System section.

Impacts to Data Sheet: See above details.

Reason for Change: To Improve Productivity

Change Implementation Status: Complete

Date Document Changes Effective: 30 Mar 2026

NOTE: Please be advised that this is a change to the document only the product has not been changed.

Markings to Distinguish Revised from Unrevised Devices: N/A

Attachments:

DSC12x2/3/4 - High Performance Differential MEMS Oscillators

Please contact your local [Microchip sales office](#) with questions or concerns regarding this notification.

Terms and Conditions:

If you wish to receive Microchip PCNs via email please register for our PCN email service at our [PCN home page](#) select register then fill in the required fields. You will find instructions about registering for Microchips PCN email service in the [PCN FAQ](#) section.

If you wish to change your PCN profile, including opt out, please go to the [PCN home page](#) select login and sign into your myMicrochip account. Select a profile option from

Affected Catalog Part Numbers (CPN)

DSC1203CI3-133M3333

DSC1222CI2-125M0000

DSC1222CI2-156M2500

DSC1223CI2-156M0000

DSC1223CI2-156M2500

DSC1223CI2-180M0000

DSC1223CI2-133M3333

DSC1222CI2-155M5200

DSC1222CI2-25M00000

DSC1202CI3-106M2500

DSC1222CI2-212M5000

DSC1224CI2-38M40000

DSC1222CI1-156M2500

DSC1204CI2-100M0000

DSC1223CI1-100M0000

DSC1223CI3-125M0000

DSC1204CI2-148M5000

DSC1203CI2-148M5000

DSC1223CI3-148M5000

DSC1223CI2-100M0000

DSC1222CI2-156M2935

DSC1223CI3-429M5000

DSC1203CI3-200M0000

DSC1203CI3-125M0000

DSC1203CI3-106M2500

DSC1223CI3-26M00000

DSC1222CI3-164M4257

DSC1224CI3-350M0000

DSC1223CI3-100M0000

DSC1212CI3-C0029

DSC1214CI3-C0020

DSC1203CI2-400M0000

DSC1223CI1-20M00000

DSC1223CI1-66M66666

DSC1204CI3-100M0000

DSC1223CI2-27M00000

DSC1223CI2-148M5000

DSC1223CI1-50M00000

DSC1223CI1-65M00000

DSC1224CI3-156M2500

DSC1204CI1-100M0000

DSC1204CI1-161M1328

DSC1204CI2-83M25000

DSC1222CI1-125M0000

DSC1223CI1-125M0000

DSC1204CI2-161M1328

DSC1213CI3-C0020

DSC1203CI2-26M00000

DSC1223CI3-74M25000

DSC1223CI3-156M2500

DSC1224CI3-100M0000

DSC1203CI3-26M00000

DSC1223CI1-62M00000

DSC1223CI3-128M0000

DSC1222CI2-312M5000

DSC1223BI2-156M2500

DSC1223BI1-200M0000

DSC1223BI1-148M5000

DSC1203BI2-100M0000

DSC1223BI2-100M0000

DSC1203BI3-300M0000

DSC1224BI1-156M2500

DSC1223BI2-50M00000

DSC1223BI2-66M66660

DSC1224BI2-100M0000

DSC1222BI1-51M00000

DSC1202BI2-125M0000

DSC1203BI2-200M0000

DSC1203BI2-125M0000

DSC1203BI2-270M0000

DSC1223BI1-155M5200

DSC1223BI3-26M00000

DSC1222BI1-125M0000

DSC1223BI3-25M00000

DSC1223BI1-100M0000

DSC1223BI1-106M2500

DSC1223BI3-87M35154

DSC1223BI3-135M0000

DSC1223BI2-167M7721

DSC1203BI3-125M0000

DSC1224BI1-400M0000

DSC1223BI2-125M0000

DSC1222BI2-156M2539

DSC1223BI3-100M0000

DSC1203NI2-148M5000

DSC1203NI1-100M0000

DSC1222NI2-156M2500

DSC1222NI2-150M0000

DSC1224NI3-156M2500

DSC1213NI2-C0019

DSC1203NI2-148M3500

DSC1223NI1-100M0000

DSC1223NI1-135M0000

DSC1223NI1-106M2500

DSC1223NI1-148M5000

DSC1223NI1-125M0000

DSC1223NI1-156M0000

DSC1223NI1-156M2500

DSC1203NI3-148M3500

DSC1222NI1-50M00000

DSC1203NI3-200M0000

DSC1203NI3-125M0000

DSC1212NI1-C0027

DSC1203NI2-100M0000

DSC1204NI1-100M0000

DSC1223NI2-250M0000

DSC1223NI2-100M0000

DSC1223NI3-200M0000

DSC1223NI3-233M3333

DSC1203NI2-94M95000

DSC1222NI3-25M00060

DSC1223NI1-200M0000

DSC1223NI3-166M0000

DSC1203NI3-375M0000

DSC1203NI3-3M900000

DSC1223NI3-3M900000

DSC1202DI3-156M0000

DSC1203DI3-156M0000

DSC1223DI2-148M3516

DSC1223DI2-148M5000

DSC1223DI2-156M2500

DSC1203DI3-100M0000

DSC1252DI1-156M2500

DSC1223DI3-200M0000

DSC1223DI2-150M0000

DSC1224DI2-125M0000

DSC1222DI2-156M2500

DSC1223DI2-212M5000

DSC1203DI3-156M2500

DSC1213DI2-C0020

DSC1223DI1-100M0000

DSC1202DI1-156M2500

DSC1223DI1-80M00000

DSC1223DI1-50M00000

DSC1224DI1-100M0000

DSC1204DI2-148M5000

DSC1203DI2-148M5000

DSC1222DI2-121M1090

DSC1224DI3-100M0000

DSC1203DI2-270M0000

DSC1203DI2-125M0000

DSC1204DI3-156M2500

DSC1223DI2-100M0000

DSC1204DI2-100M0000

DSC1213DI2-C0033

DSC1204DI2-400M0000

DSC1224DI2-400M0000

DSC1224DI1-400M0000

DSC1223DI3-100M0000

DSC1223DI2-125M0000

DSC1223DI1-156M2500

DSC1222DI1-156M2500

DSC1204DI1-156M2500

DSC1224DI1-156M2500

DSC1222DI3-27M00000

DSC1223DI2-159M3750

DSC1223DI3-125M0000

DSC1223DI3-300M0000

DSC1223DI3-275M0000

DSC1223DI1-75M00000

DSC1223DI1-135M0000

DSC1203DI2-135M0000

DSC1223CE3-40M00000

DSC1223CE3-80M00000

DSC1223CL3-156M2500

DSC1202CE3-106M2500

DSC1203CE2-75M00000

DSC1223CL1-156M2500

DSC1222CE2-125M0000

DSC1214CL3-C0020

DSC1213CL3-C0020

DSC1223CL1-100M0000

DSC1224CL1-100M0000

DSC1203CE2-167M7722

DSC1203CL3-130M0000

DSC1202CL3-130M0000

DSC1223CE2-125M0000

DSC1222CE2-155M5200

DSC1224CL2-156M2500

DSC1224CL2-100M0000

DSC1223CL2-50M00000

DSC1223CL2-100M0000

DSC1223CL2-125M0000

DSC1223CL2-156M2500

DSC1223CL2-312M5000

DSC1223CL2-200M0000

DSC1223CL2-148M5000

DSC1203CL3-160M0000

DSC1203CL3-165M0000

DSC1223CE1-322M2656
DSC1202CL3-50M00000
DSC1224CE2-50M00000
DSC1224CE2-125M0000
DSC1222CL1-106M2500
DSC1222CL1-148M5000
DSC1223CL3-100M6633
DSC1223CL3-125M0000
DSC1223CL1-106M2500
DSC1223CL1-125M0000
DSC1223CL1-132M8125
DSC1223CL1-63M00000
DSC1223CL1-74M25000
DSC1223CL1-166M6667
DSC1224CL1-161M1328
DSC1204BL3-122M8800
DSC1204BL3-100M0000
DSC1253BE1-156M2500
DSC1203BE1-312M5000
DSC1203BE3-148M5000
DSC1203BE3-100M0000
DSC1202BE3-75M00000
DSC1253BL2-148M5000
DSC1253BL2-148M3500
DSC1224BL2-100M0000
DSC1253BL3-94M00000
DSC1213BL2-C0036
DSC1224BL2-156M2500
DSC1223BL1-312M5000
DSC1202NE2-156M2600
DSC1204NL3-122M8800
DSC1204NL3-100M0000

DSC1204NL1-100M0000

DSC1202NE2-156M2617

DSC1203NE1-125M0000

DSC1223NE1-125M0000

DSC1202NE3-75M00000

DSC1222NL3-10M00000

DSC1203NE3-15M00000

DSC1223NE3-15M00000

DSC1203NE3-120M0000

DSC1224NL3-100M0000

DSC1222NE1-100M0000

DSC1202NE2-156M2500

DSC1223NE2-100M0000

DSC1202NE1-52M50000

DSC1202NE1-46M87500

DSC1203NL1-208M1250

DSC1224NL2-100M0000

DSC1213NL3-C0037

DSC1203NE1-64M00000

DSC1222DL1-156M2500

DSC1203DL2-100M0000

DSC1224DL1-100M0000

DSC1202DL1-156M2500

DSC1222DE2-445M5000

DSC1222DL3-156M2500

DSC1203DL2-125M0000

DSC1223DE3-148M5000

DSC1223DL2-200M0000

DSC1223DL2-100M0000

DSC1224DL2-100M0000

DSC1224DL3-156M2500

DSC1222DL3-100M0000

DSC1223DL1-156M2500
DSC1223DE1-124M8000
DSC1224DL3-27M00000
DSC1224DE2-50M00000
DSC1224DE2-125M0000
DSC1223CE3-40M00000T
DSC1223CE3-80M00000T
DSC1223CL3-156M2500T
DSC1202CE3-106M2500T
DSC1203CE2-75M00000T
DSC1223CL1-156M2500T
DSC1222CE2-125M0000T
DSC1214CL3-C0020T
DSC1213CL3-C0020T
DSC1223CL1-100M0000T
DSC1224CL1-100M0000T
DSC1203CE2-167M7722T
DSC1203CL3-130M0000T
DSC1202CL3-130M0000T
DSC1223CE2-125M0000T
DSC1222CE2-155M5200T
DSC1224CL2-156M2500T
DSC1224CL2-100M0000T
DSC1223CL2-50M00000T
DSC1223CL2-100M0000T
DSC1223CL2-125M0000T
DSC1223CL2-156M2500T
DSC1223CL2-312M5000T
DSC1223CL2-200M0000T
DSC1223CL2-148M5000T
DSC1203CL3-160M0000T
DSC1203CL3-165M0000T

DSC1223CE1-322M2656T
DSC1202CL3-50M00000T
DSC1224CE2-50M00000T
DSC1224CE2-125M0000T
DSC1222CL1-106M2500T
DSC1222CL1-148M5000T
DSC1223CL3-100M6633T
DSC1223CL3-125M0000T
DSC1223CL1-106M2500T
DSC1223CL1-125M0000T
DSC1223CL1-132M8125T
DSC1223CL1-63M00000T
DSC1223CL1-74M25000T
DSC1223CL1-166M6667T
DSC1224CL1-161M1328T
DSC1204BL3-122M8800T
DSC1204BL3-100M0000T
DSC1253BE1-156M2500T
DSC1203BE1-312M5000T
DSC1203BE3-148M5000T
DSC1203BE3-100M0000T
DSC1202BE3-75M00000T
DSC1253BL2-148M5000T
DSC1253BL2-148M3500T
DSC1224BL2-100M0000T
DSC1253BL3-94M00000T
DSC1213BL2-C0036T
DSC1224BL2-156M2500T
DSC1223BL1-312M5000T
DSC1202NE2-156M2600T
DSC1204NL3-122M8800T
DSC1204NL3-100M0000T

DSC1204NL1-100M0000T
DSC1202NE2-156M2617T
DSC1203NE1-125M0000T
DSC1223NE1-125M0000T
DSC1202NE3-75M00000T
DSC1222NL3-10M00000T
DSC1203NE3-15M00000T
DSC1223NE3-15M00000T
DSC1203NE3-120M0000T
DSC1224NL3-100M0000T
DSC1222NE1-100M0000T
DSC1202NE2-156M2500T
DSC1223NE2-100M0000T
DSC1202NE1-52M50000T
DSC1202NE1-46M87500T
DSC1203NL1-208M1250T
DSC1224NL2-100M0000T
DSC1213NL3-C0037T
DSC1203NE1-64M00000T
DSC1222DL1-156M2500T
DSC1203DL2-100M0000T
DSC1224DL1-100M0000T
DSC1202DL1-156M2500T
DSC1222DE2-445M5000T
DSC1222DL3-156M2500T
DSC1203DL2-125M0000T
DSC1223DE3-148M5000T
DSC1223DL2-200M0000T
DSC1223DL2-100M0000T
DSC1224DL2-100M0000T
DSC1224DL3-156M2500T
DSC1222DL3-100M0000T

DSC1223DL1-156M2500T
DSC1223DE1-124M8000T
DSC1224DL3-27M00000T
DSC1224DE2-50M00000T
DSC1224DE2-125M0000T
DSC1203CI2-100M0000T
DSC1203CI3-100M0000T
DSC1222CI3-156M2500T
DSC1224CI2-100M0000T
DSC1203CI3-133M3300T
DSC1203CI3-133M3333T
DSC1222CI2-125M0000T
DSC1222CI2-156M2500T
DSC1223CI2-156M0000T
DSC1223CI2-156M2500T
DSC1223CI2-180M0000T
DSC1223CI2-133M3333T
DSC1222CI2-155M5200T
DSC1222CI2-25M00000T
DSC1202CI3-106M2500T
DSC1222CI2-212M5000T
DSC1224CI2-38M40000T
DSC1222CI1-156M2500T
DSC1204CI2-100M0000T
DSC1223CI1-100M0000T
DSC1223CI3-125M0000T
DSC1204CI2-148M5000T
DSC1203CI2-148M5000T
DSC1223CI3-148M5000T
DSC1223CI2-100M0000T
DSC1222CI2-156M2935T
DSC1223CI3-429M5000T

DSC1203CI3-200M0000T
DSC1203CI3-125M0000T
DSC1203CI3-106M2500T
DSC1223CI3-26M00000T
DSC1222CI3-164M4257T
DSC1224CI3-350M0000T
DSC1223CI3-100M0000T
DSC1212CI3-C0029T
DSC1214CI3-C0020T
DSC1203CI2-400M0000T
DSC1223CI1-20M00000T
DSC1223CI1-66M66666T
DSC1204CI3-100M0000T
DSC1223CI2-27M00000T
DSC1223CI2-148M5000T
DSC1223CI1-50M00000T
DSC1223CI1-65M00000T
DSC1224CI3-156M2500T
DSC1204CI1-100M0000T
DSC1204CI1-161M1328T
DSC1204CI2-83M25000T
DSC1222CI1-125M0000T
DSC1223CI1-125M0000T
DSC1204CI2-161M1328T
DSC1213CI3-C0020T
DSC1203CI2-26M00000T
DSC1223CI3-74M25000T
DSC1223CI3-156M2500T
DSC1224CI3-100M0000T
DSC1203CI3-26M00000T
DSC1223CI1-62M00000T
DSC1223CI3-128M0000T

DSC1222CI2-312M5000T

DSC1223BI2-156M2500T

DSC1223BI1-200M0000T

DSC1223BI1-148M5000T

DSC1203BI2-100M0000T

DSC1223BI2-100M0000T

DSC1203BI3-300M0000T

DSC1224BI1-156M2500T

DSC1223BI2-50M00000T

DSC1223BI2-66M66660T

DSC1224BI2-100M0000T

DSC1222BI1-51M00000T

DSC1202BI2-125M0000T

DSC1203BI2-200M0000T

DSC1203BI2-125M0000T

DSC1203BI2-270M0000T

DSC1223BI1-155M5200T

DSC1223BI3-26M00000T

DSC1222BI1-125M0000T

DSC1223BI3-25M00000T

DSC1223BI1-100M0000T

DSC1223BI1-106M2500T

DSC1223BI3-87M35154T

DSC1223BI3-135M0000T

DSC1223BI2-167M7721T

DSC1203BI3-125M0000T

DSC1224BI1-400M0000T

DSC1223BI2-125M0000T

DSC1222BI2-156M2539T

DSC1223BI3-100M0000T

DSC1203NI2-148M5000T

DSC1203NI1-100M0000T

DSC1222NI2-156M2500T

DSC1222NI2-150M0000T

DSC1224NI3-156M2500T

DSC1213NI2-C0019T

DSC1203NI2-148M3500T

DSC1223NI1-100M0000T

DSC1223NI1-135M0000T

DSC1223NI1-106M2500T

DSC1223NI1-148M5000T

DSC1223NI1-125M0000T

DSC1223NI1-156M0000T

DSC1223NI1-156M2500T

DSC1203NI3-148M3500T

DSC1222NI1-50M00000T

DSC1203NI3-200M0000T

DSC1203NI3-125M0000T

DSC1212NI1-C0027T

DSC1203NI2-100M0000T

DSC1204NI1-100M0000T

DSC1223NI2-250M0000T

DSC1223NI2-100M0000T

DSC1223NI3-200M0000T

DSC1223NI3-233M3333T

DSC1203NI2-94M95000T

DSC1222NI3-25M00060T

DSC1223NI1-200M0000T

DSC1223NI3-166M0000T

DSC1203NI3-375M0000T

DSC1203NI3-3M900000T

DSC1223NI3-3M900000T

DSC1202DI3-156M0000T

DSC1203DI3-156M0000T

DSC1223DI2-148M3516T

DSC1223DI2-148M5000T

DSC1223DI2-156M2500T

DSC1203DI3-100M0000T

DSC1252DI1-156M2500T

DSC1223DI3-200M0000T

DSC1223DI2-150M0000T

DSC1224DI2-125M0000T

DSC1222DI2-156M2500T

DSC1223DI2-212M5000T

DSC1203DI3-156M2500T

DSC1213DI2-C0020T

DSC1223DI1-100M0000T

DSC1202DI1-156M2500T

DSC1223DI1-80M00000T

DSC1223DI1-50M00000T

DSC1224DI1-100M0000T

DSC1204DI2-148M5000T

DSC1203DI2-148M5000T

DSC1222DI2-121M1090T

DSC1224DI3-100M0000T

DSC1203DI2-270M0000T

DSC1203DI2-125M0000T

DSC1204DI3-156M2500T

DSC1223DI2-100M0000T

DSC1204DI2-100M0000T

DSC1213DI2-C0033T

DSC1204DI2-400M0000T

DSC1224DI2-400M0000T

DSC1224DI1-400M0000T

DSC1223DI3-100M0000T

DSC1223DI2-125M0000T

DSC1223DI1-156M2500T

DSC1222DI1-156M2500T

DSC1204DI1-156M2500T

DSC1224DI1-156M2500T

DSC1222DI3-27M00000T

DSC1223DI2-159M3750T

DSC1223DI3-125M0000T

DSC1223DI3-300M0000T

DSC1223DI3-275M0000T

DSC1223DI1-75M00000T

DSC1223DI1-135M0000T

DSC1203DI2-135M0000T

DSC1223CA2-156M2500T

DSC1213CA3-C0026T

DSC1203CA3-100M0000T

DSC1203CA3-125M0000T

DSC1213CA2-C0020T

DSC1223CA2-27M00000T

DSC1203CA3-200M0000T

DSC1223CA1-333M0000T

DSC1223CA1-222M0000T

DSC1223CA1-111M0000T

DSC1223CA3-125M0000T

DSC1204BA2-125M0000T

DSC1213BA1-C0038T

DSC1203NA1-20M00000T

DSC1203NA1-156M2500T

DSC1223NA2-106M2500T

DSC1223DA2-156M2500T

DSC1223DA3-100M0000T

DSC1203DA3-333M3333T

DSC1203DA3-83M33333T

DSC1213DA3-C0035T

DSC1223DA2-100M0000T

DSC1223DA1-5M000000T

DSC1223DA1-100M0000T

DSC1223DA1-122M8800T

DSC1223DA1-3M840000T

DSC1223CA1-156M2500

DSC1223CA1-100M0000

DSC1203DA3-156M0000

DSC1222CI3-312M5000

DSC1224CI1-100M0000

DSC1223CI2-75M00000

DSC1223CI3-75M00000

DSC1223CI1-60M00000

DSC1223CI1-156M2500

DSC1222CI2-300M0000

DSC1203CI3-120M0000

DSC1224CI3-24M00000

DSC1203CI3-74M17500

DSC1222BA1-156M2500

DSC1223BI3-75M00000

DSC1222NA1-156M2500

DSC1223NI1-60M00000

DSC1223DI2-75M00000

DSC1223DI3-75M00000

DSC1224DI1-40M00000

DSC1223DI1-150M0000

DSC1203DI2-400M0000

DSC1203DI2-108M0000

DSC1224DI2-100M0000

DSC1223CL3-72M00000

DSC1223CL3-74M25000

DSC1223CL3-74M17582
DSC1224BL1-156M2500
DSC1223CL3-72M00000T
DSC1223CL3-74M25000T
DSC1223CL3-74M17582T
DSC1224BL1-156M2500T
DSC1222CI3-312M5000T
DSC1224CI1-100M0000T
DSC1223CI2-75M00000T
DSC1223CI3-75M00000T
DSC1223CI1-60M00000T
DSC1223CI1-156M2500T
DSC1222CI2-300M0000T
DSC1203CI3-120M0000T
DSC1224CI3-24M00000T
DSC1203CI3-74M17500T
DSC1223BI3-75M00000T
DSC1223NI1-60M00000T
DSC1223DI2-75M00000T
DSC1223DI3-75M00000T
DSC1224DI1-40M00000T
DSC1223DI1-150M0000T
DSC1203DI2-400M0000T
DSC1203DI2-108M0000T
DSC1224DI2-100M0000T
DSC1223CA1-156M2500T
DSC1223CA1-100M0000T
DSC1203DA3-156M0000T
DSC1223DA2-156M2500
DSC1223DA3-100M0000
DSC1203DA3-333M3333
DSC1203DA3-83M33333

DSC1213DA3-C0035

DSC1223DA2-100M0000

DSC1223DA1-5M000000

DSC1223DA1-100M0000

DSC1223DA1-122M8800

DSC1223DA1-3M840000

DSC1203CI2-100M0000

DSC1203CI3-100M0000

DSC1222CI3-156M2500

DSC1224CI2-100M0000

DSC1203CI3-133M3300

DSC1223CA2-156M2500

DSC1213CA3-C0026

DSC1203CA3-100M0000

DSC1203CA3-125M0000

DSC1213CA2-C0020

DSC1223CA2-27M00000

DSC1203CA3-200M0000

DSC1223CA1-333M0000

DSC1223CA1-222M0000

DSC1223CA1-111M0000

DSC1223CA3-125M0000

DSC1204BA2-125M0000

DSC1213BA1-C0038

DSC1203NA1-20M00000

DSC1203NA1-156M2500

DSC1223NA2-106M2500

High Performance Differential MEMS Oscillators

Features

- Very Low RMS Phase Jitter: <650 fs (typ.)
- High Stability: ± 20 ppm, ± 25 ppm, ± 50 ppm
- Wide Temperature Range:
 - Automotive: -40°C to $+125^{\circ}\text{C}$ (DSC12x LVDS Only)
 - For AEC-Q100 qualified parts, refer to DSA1200 Family
 - Ext. Industrial: -40°C to $+105^{\circ}\text{C}$
 - Industrial: -40°C to $+85^{\circ}\text{C}$
 - Commercial: -20°C to $+70^{\circ}\text{C}$
- Supports LVPECL, LVDS, or HCSL Differential Outputs
- PCIe Gen1-7 Compliant Output
- Wide Frequency Range: 2.5 MHz to 450 MHz
- Small Industry Standard Footprints:
 - 2.5 mm x 2.0 mm
 - 3.2 mm x 2.5 mm
 - 5.0 mm x 3.2 mm
 - 7.0 mm x 5.0 mm
- Excellent Shock and Vibration Immunity
 - Qualified to MIL-STD-883
- High Reliability
 - 20x Better MTF than Quartz Oscillators
- Supply Range of 2.25 to 3.6V
- Standby, Frequency Select, and Output Enable Functions
- Lead-Free and RoHS Compliant

Applications

- Storage Area Networks
- Passive Optical Networks
- 10/100G Ethernet
- HD/SD/SDI Video and Surveillance
- PCI Express Gen 1/2/3/4/5/6/7
- Display Port


General Description

The DSC12x2/3/4 family of high performance oscillators utilizes the latest generation of silicon MEMS technology that reduces close-in noise and provides excellent jitter and stability over a wide range of supply voltages and temperatures. By eliminating the need for quartz or SAW technology, MEMS oscillators significantly enhance reliability and accelerate product development, while meeting stringent clock performance criteria for a variety of communications, storage, and networking applications.

The DSC12x2/3/4 family features a control function on pin 1 or pin 2 that permits either a standby feature (complete power down when $\overline{\text{STDBY}}$ is low), output enable (output is tri-stated with OE low), or a frequency select (choice of two frequencies selected by FS high/low). See the Product Identification System section for detailed information.


All oscillators are available in industry-standard packages, including the small 2.5 mm x 2.0 mm, and are “drop-in” replacements for standard 6-pin LVPECL/LVDS/HCSL crystal oscillators.

Package Types



DSC12X2/3/4

Functional Block Diagrams



1.0 ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings †

Supply Voltage	–0.3V to +4.0V
Input Voltage	–0.3V to $V_{DD} + 0.3V$
ESD Protection (HBM)	4 kV
ESD Protection (MM)	400V
ESD Protection (CDM)	1.5 kV

† **Notice:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

TABLE 1-1: ELECTRICAL CHARACTERISTICS

Electrical Characteristics: $V_{DD} = 2.5V \pm 10\%$ or $3.3V \pm 10\%$; $T_A = -40^\circ C$ to $+105^\circ C$, unless noted.

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Supply Voltage	V_{DD}	2.25	—	3.63	V	Note 1
Supply Current	I_{DD}	—	50	—	mA	LVPECL, $f_{OUT} = 100$ MHz
		—	32	—		LVDS, $f_{OUT} = 100$ MHz
		—	40	—		HCSL, $f_{OUT} = 100$ MHz
		—	23	—		Output disabled (tri-state), $f_{OUT} = 100$ MHz
Standby Current	$I_{STDBY_}$	—	2.5	5	μA	Input pin = $\overline{STDBY}$ = Asserted, ($V_{DD} = 3.3V$)
Frequency Stability	Δf	—	—	± 20	ppm	Includes frequency variations due to initial tolerance, temp., and power supply voltage
		—	—	± 25		
		—	—	± 50		
Aging	Δf	—	—	± 5	ppm	First year @ $25^\circ C$
		—	—	± 1		Per year after first year
Startup Time	t_{SU}	—	5.5	6	ms	From 90% V_{DD} to valid clock output, $T = +25^\circ C$, Note 2
Input Logic Levels	V_{IH}	$0.75 \times V_{DD}$	—	—	V	Input logic high
	V_{IL}	—	—	$0.25 \times V_{DD}$		Input logic low
Output Disable Time	t_{DA}	—	—	25	ns	Note 3
Output Enable Time	t_{EN}	—	—	6	ms	$\overline{STDBY}$
		—	—	350	ns	OE
Enable Pull-Up Resistor	—	—	1.5	—	M Ω	Pull-up resistor on pin 1, Note 4

Note 1: V_{DD} pin should be filtered with 0.1 μF capacitor.

2: t_{SU} is time to 100 ppm stable output frequency after V_{DD} is applied and outputs are enabled.

3: t_{DA} : See the Output Waveforms and the Test Circuits sections for more information.

4: Output is enabled if pad is floated (not connected).

5: Jitter limits are established by Gen 1.1, Gen 2.1, and Gen 3.0 PCIe standards.

DSC12X2/3/4

TABLE 1-1: ELECTRICAL CHARACTERISTICS (CONTINUED)

Electrical Characteristics: $V_{DD} = 2.5V \pm 10\%$ or $3.3V \pm 10\%$; $T_A = -40^\circ C$ to $+105^\circ C$, unless noted.

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
LVPECL (DSC12x2)						
Frequency	f_0	2.5	—	450	MHz	—
Output Logic Levels	V_{OH}	$V_{DD} - 1.145$	—	—	V	$R_L = 50\Omega$
	V_{OL}	—	—	$V_{DD} - 1.695$		
Peak-to-Peak Output Swing	V_{PP}	—	800	—	mV	Single-Ended
Output Transition Time	t_R	—	200	250	ps	20% to 80%, $R_L = 50\Omega$
	t_F	—	250	300		
Output Duty Cycle	SYM	48	—	52	%	Differential
Period Jitter RMS	J_{PER}	—	2.0	—	ps	$f_0 = 156.25$ MHz, 10k cycles
Period Jitter Peak-to-Peak	J_{PTP}	—	20	—	ps	$f_0 = 156.25$ MHz, 10k cycles
Integrated Phase Noise (Random)	J_{PH}	—	0.65	—	ps_{RMS}	12 kHz to 20 MHz @156.25 MHz
LVDS (DSC12x3)						
Frequency	f_0	2.3	—	450	MHz	—
Output Offset Voltage	V_{OS}	1.15	1.25	1.35	V	$R = 100\Omega$ Differential
Peak-to-Peak Output Swing	V_{PP}	250	350	450	mV	Single-Ended
Output Transition Time	t_R	120	170	220	ps	20% to 80%, $R_L = 100\Omega$
	t_F					
Output Duty Cycle	SYM	48	—	52	%	Differential
Period Jitter RMS	J_{PER}	—	2.5	—	ps	$f_0 = 156.25$ MHz, 10k cycles
Period Jitter Peak-to-Peak	J_{PTP}	—	20	—	ps	$f_0 = 156.25$ MHz, 10k cycles
Period Jitter RMS	J_{PER}	—	3	—	ps	$f_0 = 156.25$ MHz, $T_A = -40^\circ C$ to $+125^\circ C$
Period Jitter Peak-to-Peak	J_{PTP}	—	25	—	ps	$f_0 = 156.25$ MHz, $T_A = -40^\circ C$ to $+125^\circ C$
Integrated Phase Noise (Random)	J_{PH}	—	0.65	—	ps_{RMS}	12 kHz to 20 MHz @156.25 MHz, $T_A = -40^\circ C$ to $+105^\circ C$
		—	0.9	—		2 kHz to 20 MHz @156.25 MHz, $T_A = -40^\circ C$ to $+105^\circ C$
Phase Jitter	J_{RMS-CC}	—	0.025	0.1	ps_{RMS}	PCIe Gen 6.0, 64 GT/s

Note 1: V_{DD} pin should be filtered with 0.1 μF capacitor.

2: t_{SU} is time to 100 ppm stable output frequency after V_{DD} is applied and outputs are enabled.

3: t_{DA} : See the Output Waveforms and the Test Circuits sections for more information.

4: Output is enabled if pad is floated (not connected).

5: Jitter limits are established by Gen 1.1, Gen 2.1, and Gen 3.0 PCIe standards.

TABLE 1-1: ELECTRICAL CHARACTERISTICS (CONTINUED)

Electrical Characteristics: $V_{DD} = 2.5V \pm 10\%$ or $3.3V \pm 10\%$; $T_A = -40^\circ C$ to $+105^\circ C$, unless noted.

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
HCSL (DSC12x4)						
Frequency	f_0	2.3	—	450	MHz	—
Output Logic Levels	V_{OH}	0.64	—	—	V	$R_L = 50\Omega$
	V_{OL}	—	—	0.1		
Peak-to-Peak Output Swing	V_{PP}	—	750	—	mV	Single-Ended
Output Transition Time	t_R	200	260	400	ps	20% to 80%, $R_L = 50\Omega$
	t_F	250	370	500		
Output Duty Cycle	SYM	48	—	52	%	Differential
Period Jitter RMS	J_{PER}	—	2	—	ps	$f_0 = 100.00$ MHz, 10k cycles
Period Jitter Peak-to-Peak	J_{PTP}	—	16	—	ps	$f_0 = 100.00$ MHz, 10k cycles
Integrated Phase Noise (Random)	J_{PH}	—	0.617	—	$pSRMS$	12 kHz to 20 MHz @100 MHz $T_A = -40^\circ C$ to $+105^\circ C$
		—	0.460	—		100 kHz to 20 MHz @100 MHz $T_A = -40^\circ C$ to $+105^\circ C$
		—	0.212	—		1.875 MHz to 20 MHz @100 MHz $T_A = -40^\circ C$ to $+105^\circ C$
Phase Jitter	T_J	—	3.42	86	ps_{PP}	PCIe Gen 1.1, $T_J = D_J + 14.069 \times R_J$ (BER 10^{-12}), Note 5
	$J_{RMS-CCHF}$	—	0.247	3.1	$pSRMS$	PCIe Gen 2.1, 1.5 MHz to Nyquist, Note 5
	$J_{RMS-CCHF}$	—	0.08	3.0	$pSRMS$	PCIeGen2.1, 10 kHz to 1.5 MHz, Note 5
	J_{RMS-CC}	—	0.107	1.0	$pSRMS$	PCIe Gen 3.0, Note 5
		—	0.107	0.30		PCIe Gen 4.0, 16 GT/s
		—	0.043	0.12		PCIe Gen 5.0, 32 GT/s
		—	0.054	0.1		PCIe Gen 6.0, 64 GT/s
		—	0.038	0.067		PCIe Gen 7.0, 128 GT/s

Note 1: V_{DD} pin should be filtered with 0.1 μF capacitor.

2: t_{SU} is time to 100 ppm stable output frequency after V_{DD} is applied and outputs are enabled.

3: t_{DA} : See the Output Waveforms and the Test Circuits sections for more information.

4: Output is enabled if pad is floated (not connected).

5: Jitter limits are established by Gen 1.1, Gen 2.1, and Gen 3.0 PCIe standards.

DSC12X2/3/4

TEMPERATURE SPECIFICATIONS (Note 1)

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Temperature Ranges						
Maximum Junction Temperature	T_J	—	—	+150	°C	—
Storage Temperature Range	T_S	–55	—	+150	°C	—
Lead Temperature	—	—	—	+260	°C	Soldering, 40 sec.

Note 1: The maximum allowable power dissipation is a function of ambient temperature, the maximum allowable junction temperature and the thermal resistance from junction to air (i.e., T_A , T_J , θ_{JA}). Exceeding the maximum allowable power dissipation will cause the device operating junction temperature to exceed the maximum +125°C rating. Sustained junction temperatures above +125°C can impact the device reliability.

2.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in [Table 2-1](#) and [Table 2-2](#).

TABLE 2-1: DSC120x/1x/2x PIN FUNCTION TABLE

Pin Number	Pin Name	Description
1	OE/ $\overline{\text{STDBY}}$ /FS	Control pin: Output enable/standby/frequency select.
2	NC	No connect.
3	GND	Power supply ground.
4	CLK+	Clock output +.
5	CLK–	Clock output –.
6	VDD	Power supply.

TABLE 2-2: DSC123x/4x/5x PIN FUNCTION TABLE

Pin Number	Pin Name	Description
1	NC	No connect.
2	OE/ $\overline{\text{STDBY}}$ /FS	Control pin: Output enable/standby/frequency select.
3	GND	Power supply ground.
4	CLK+	Clock output +.
5	CLK–	Clock output –.
6	VDD	Power supply.

DSC12X2/3/4

3.0 TERMINATION SCHEME




FIGURE 3-1: LVPECL Termination (DSC12x2).

In [Figure 3-1](#), Thevenin termination for 3.3V operation. Values will differ for $V_{DD} = 2.5V$




FIGURE 3-2: LVDS Termination (DSC12x3).




FIGURE 3-3: HCSL Termination (DSC12x4).

4.0 OUTPUT WAVEFORM




FIGURE 4-1: LVPECL, LVDS, and HCSL Output Waveform.

TABLE 4-1: OUTPUT VOLTAGE SWING BY LOGIC TYPE

Output Logic Protocol	Typical Peak-to-Peak Output Swing
LVPECL	830 mV
LVDS	350 mV
HCSL	675 mV

5.0 TEST CIRCUITS




FIGURE 5-1: LVPECL Test Circuit.




FIGURE 5-2: LVDS Test Circuit.




FIGURE 5-3: HCSL Test Circuit.

6.0 SOLDER REFLOW PROFILE




FIGURE 6-1: Solder Reflow Profile.

TABLE 6-1: SOLDER REFLOW

MSL 1 @ 260°C refer to JSTD-020C	
Ramp-Up Rate (200°C to Peak Temp)	3°C/Sec. Max.
Preheat Time 150°C to 200°C	60-180 Sec.
Time Maintained Above 217°C	60-150 Sec.
Peak Temperature	255°C to 260°C
Time within 5°C of Actual Peak	20-40 Sec.
Ramp-Down Rate	6°C/Sec. Max.
Time 25°C to Peak Temperature	8 minute Max.

DSC12X2/3/4

7.0 BOARD LAYOUT (RECOMMENDED)




FIGURE 7-1: DSC12x2/3/4 Recommended Board Layout.

8.0 PHASE NOISE




FIGURE 8-1: DSC12x4 Phase Noise at 100 MHz.

DSC12X2/3/4





FIGURE 8-2: DSC12x2 Phase Noise at 156.25 MHz.


9.0 PACKAGING INFORMATION

9.1 Package Marking Information

6-Lead VDFN*




Example



Legend:	XX...X	Product code, customer-specific information, or frequency in MHz without printed decimal point
	Y	Year code (last digit of calendar year)
	YY	Year code (last 2 digits of calendar year)
	WW	Week code (week of January 1 is week '01')
	SSS	Alphanumeric traceability code
	(e3)	Pb-free JEDEC® designator for Matte Tin (Sn)
	*	This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package.
	•, ▲, ▼	Pin one index is identified by a dot, delta up, or delta down (triangle)
Note:	In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo.	
	Underbar (_) and/or Overbar (¯) symbol may not be to scale.	

6-Lead Very Thin Dual Flatpack No-Leads (J7A) - 2.5x2.0 mm Body [VDFN]


Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing C04-1005-J7A Rev E Sheet 1 of 2

6-Lead Very Thin Dual Flatpack No-Leads (J7A) - 2.5x2.0 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	6		
Pitch	e	0.825 BSC		
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Overall Length	D	2.50 BSC		
Overall Width	E	2.00 BSC		
Terminal Width	b1	0.60	0.65	0.70
Terminal Width	b2	0.20	0.25	0.30
Terminal Length	L1	0.60	0.70	0.80
Terminal Length	L2	0.665	0.765	0.865


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1005-J7A Rev E Sheet 2 of 2

6-Lead Very Thin Dual Flatpack No-Leads (J7A) - 2.5x2.0 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN


Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.825 BSC		
Contact Pad Width (X4)	X1			0.65
Contact Pad Width (X2)	X2			0.25
Contact Pad Length (X6)	Y			0.85
Contact Pad Spacing	C		1.45	
Space Between Contacts (X4)	G1	0.38		
Space Between Contacts (X3)	G2	0.60		

- Notes:
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3005-J7A Rev E

6-Lead Very Thin Plastic Dual Flatpack No-Lead (H5A) - 3.2x2.5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	6		
Pitch	e	1.05 BSC		
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Overall Length	D	3.20 BSC		
Overall Width	E	2.50 BSC		
Terminal Width	b1	0.85	0.90	0.95
Terminal Width	b2	0.45	0.50	0.55
Terminal Length	L	0.65	0.70	0.75
Terminal Pullback	L1	0.10 REF		

- Notes:
- 1. Pin 1 visual index feature may vary, but must be located within the hatched area.
 - 2. Package is saw singulated
 - 3. Dimensioning and tolerancing per ASME Y14.5M
- BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1007-H5A Rev C Sheet 2 of 2

6-Lead Very Thin Plastic Dual Flatpack No-Lead (H5A) - 3.2x2.5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E		1.05 BSC	
Contact Pad Spacing	C		1.60	
Contact Pad Width (X4)	X1			1.00
Contact Pad Width (X2)	X2			0.60
Contact Pad Length (X6)	Y			0.85
Space Between Contacts (X4)	G1	0.75		
Space Between Contacts (X3)	G2	0.25		
Pin 1 Index Chamfer (X4)	CH		0.25	

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


Microchip Technology Drawing C04-3007-H5A Rev C

© 2024 Microchip Technology Inc.

DSC12X2/3/4

6-Lead Very Thin Plastic Dual Flat, No Lead Package (H7A) - 3.2x5.0 x0.9 Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing C04-1009-H7A Rev B Sheet 1 of 2

© 2024 Microchip Technology Inc.

6-Lead Very Thin Plastic Dual Flat, No Lead Package (H7A) - 3.2x5.0 x0.9 Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	6		
Pitch	e	1.27 BSC		
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.203 REF		
Overall Length	D	5.00 BSC		
Overall Width	E	3.20 BSC		
Terminal Width	b	0.59	0.64	0.69
Terminal Length	L	0.90	1.00	1.10
Terminal 1 Index Chamfer	CH	0.25 REF		
Terminal-to-Terminal	K	1.20 REF		

Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1009-H7A Rev B Sheet 2 of 2

© 2024 Microchip Technology Inc.

6-Lead Very Thin Plastic Dual Flat, No Lead Package (H7A) - 3.2x5.0 x0.9 Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	1.27 BSC		
Contact Pad Spacing	C		2.30	
Contact Pad Width (X6)	X			0.64
Contact Pad Length (X6)	Y			1.10
Contact Pad to Contact Pad (X4)	G	1.20 REF		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3009-H7A Rev B

© 2024 Microchip Technology Inc.

6-Lead Very Thin Dual Flatpack, No Lead Package (HPA) - 7x5 mm Body [VDFN]


Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing C04-1227-HPA Rev B Sheet 1 of 2

6-Lead Very Thin Dual Flatpack, No Lead Package (HPA) - 7x5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	6		
Pitch	e	2.54 BSC		
Overall Height	A	0.80	0.85	0.90
Standoff	A1	0.00	0.02	0.05
Overall Length	D	7.00 BSC		
Overall Width	E	5.00 BSC		
Terminal Width	b	1.30	1.40	1.50
Terminal Length	L	1.00	1.10	1.20
Pullback	L1	0.10 REF		


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1227-HPA Rev B Sheet 2 of 2

6-Lead Very Thin Dual Flatpack, No Lead Package (HPA) - 7x5 mm Body [VDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E		2.54 BSC	
Contact Pad Spacing	C		3.90	
Contact Pad Width (X6)	X1			1.55
Contact Pad Length (X6)	Y1			1.40

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3227-HPA Rev B

© 2024 Microchip Technology Inc.

DSC12X2/3/4

NOTES:

APPENDIX A: REVISION HISTORY

Revision A (April 2019)

- Initial release of DSC12x2/3/4 as Microchip data sheet DS20006011A.

Revision B (June 2020)

- Revisions to the data sheet made in the [Electrical Characteristics](#) table under HCSL: Added new rows for Integrated Phase Noise and Phase Jitter.
- Also added a new bullet under the [Features](#) section.

Revision C (January 2021)

- Updated Phase Jitter maximum values for $J_{\text{RMS-CC}}$ in the [Electrical Characteristics](#) table and added a sixth note.
- Updated package drawing for 6-Lead VDFN 2.5 mm x 2.0 mm Package Outline and Recommended Land Pattern.
- Updated [Figure 3-1](#).

Revision D (March 2021)

- Removed Note 6 from the [Electrical Characteristics](#) table.

Revision E (March 2022)

- Added PCI Express Gen 5 to the [Applications](#) list.

Revision F (May 2023)

- Added PCI Express Gen 6 to the [Applications](#) list and the [Features](#) list.
- Corrected the maximum value for Peak-to-Peak Output Swing in the LVDS (DSC12x3) section of the [Electrical Characteristics](#) table.
- Added PCIe Gen 6 Phase Jitter values to the LVDS (DSC12x3) and HCSL (DSC12x4) sections of the [Electrical Characteristics](#) table.

Revision G (June 2025)

- Added DSA1200 reference to [Features](#) and the [Product Identification System](#) sections for customers seeking AEC-Q100 qualified parts.
- Updated the package outline drawings to the most current versions.

Revision H (October 2025)

- Fixed minimum output duty cycle value in the [Electrical Characteristics](#) table in the LVDS (DSC12x3) section.
- Added PCIe Gen 7 information to [Features](#) and [Applications](#) sections, as well as to the Phase Jitter rows of the [Electrical Characteristics](#) table.

Revision I (March 2026)

- Added a note regarding bulk quantities to the [Product Identification System](#) section.

DSC12X2/3/4

NOTES:

PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

PART NO.		X	X	X	X	X	-XXXXXXXX	X
Device		Control Pin	Output Format	Package	Temperature	Freq. Stability	Output Frequency	Media Type
Device:	DSC12:	High Performance Differential MEMS Oscillators (Note 1)						
Control Pin:	0	=	Pin 1 $\overline{\text{STDBY}}$ with Pull-up					
	1	=	Pin 1 Frequency Select with Pull-up					
	2	=	Pin 1 OE with Pull-up					
	3	=	Pin 2 $\overline{\text{STDBY}}$ with Pull-up					
	4	=	Pin 2 Frequency Select with Pull-up					
	5	=	Pin 2 OE with Pull-up					
Output Format:	2	=	LVPECL					
	3	=	LVDS					
	4	=	HCSL					
Package:	N	=	7 mm x 5 mm 6-Lead VDFN					
	B	=	5 mm x 3.2 mm 6-Lead CDFN					
	C	=	3.2 mm x 2.5 mm 6-Lead VDFN					
	D	=	2.5 mm x 2 mm 6-Lead VDFN					
Temperature:	A	=	-40°C to +125°C(Available on certain options)					
	L	=	-40°C to +105°C					
	I	=	-40°C to +85°C					
	E	=	-20°C to +70°C					
Frequency Stability:	1	=	±50 ppm					
	2	=	±25 ppm					
	3	=	±20 ppm					
Output Frequency:	xMxxxxxx=	<10 MHz						
	xxMxxxxx=	<100 MHz						
	xxxMxxxx=	>100 MHz						
	CCCCC=	with Frequency Select						
	PROG =	TimeFlash						
Media Type: (Note 2)	<blank>=	Bulk						
	T	=	1,000/Reel					
	B	=	3,000/Reel					

Examples:

a) DSC1202NE1-25M00000T: Pin 1 $\overline{\text{STDBY}}$ with Pull-up, LVPECL Output, 7x5 VDFN, -20°C to +70°C, ±50 ppm, 25 MHz Output Frequency, 1,000/Reel

b) DSC1243CL3-C0013: Pin 2 Frequency Select with Pull-up, LVDS Output, 3.2x2.5 VDFN, -40°C to +105°C, ±20 ppm, Multiple Output Frequency, Bulk

c) DSC1224BI2-19M50000B: Pin 1 OE with Pull-up, HCSL Output, 5x3.2 CDFN, -40°C to +85°C, ±25 ppm, 19.5 MHz Output Frequency, 3,000/Reel

d) DSC1232DL3-55M82000T: Pin 2 $\overline{\text{STDBY}}$ with Pull-up, LVPECL Output, 2.5x2 VDFN, -40°C to +105°C, ±20 ppm, 55.82 MHz Output Frequency, 1,000/Reel

e) DSC1213NI1-C0014B: Pin 1 Frequency Select with Pull-up, LVDS Output, 7x5 VDFN, -40°C to +85°C, ±50 ppm, Multiple Output Frequency, 3,000/Reel

Note 1: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

Please visit the [Microchip ClockWorks Configurator®](http://clockworks.microchip.com/timing) website to configure the part number for customized frequency select settings.

<http://clockworks.microchip.com/timing>

Note 1: For AEC-Q100 qualified parts, please refer to the DSA1200 family.

2: On orders for bulk CPNs, product may be supplied in either cut tape (without a reel) or tube packaging, depending on availability. For Tape & Reel orders that are <1000 pieces, product may be supplied on cut tape (without a reel) depending on availability.

DSC12X2/3/4

NOTES:

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at <https://www.microchip.com/en-us/about/legal-information/microchip-trademarks>.

ISBN: 979-8-3371-3037-8

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.