



OUTSIDE AIR

Weatherproof Outside Air, Platinum RTD

The ACI Platinum Outside Air Series features a weather proof European style, plastic enclosure with twist off cover and water tight cord grip. The sensing element contains Etched Teflon colored lead wires to differentiate the different sensor types. The three-wire “-3W” option should be ordered if using with a 3-Wire temperature transmitter or sensor configuration on your building management system or PLC (Programmable Logic Controller). The purpose of the 3rd wire is to compensate for external lead wire resistance that will affect your sensors output signal. ACI recommends the use of 18 AWG lead wires to reduce external lead wire resistance when using a Platinum RTD sensor. The sensors in this series are manufactured using ACI’s proven double encapsulation process to eliminate the effects of moisture on the sensor

and to increase response time using our high quality, thermally conductive epoxy. The outdoor air sensor is a single point sensor designed to be mounted under an eave or on the North side of a building in a shaded location with the sensing tube pointed downward. Optional NEMA 4X “-4X” plastic or NEMA 3R “-BB” weatherproof Aluminum enclosures and NIST Certificates are available as referenced on the back of the product data sheet. For Applications in which the sensor must be mounted in direct sunlight, please see the Sun Shield data sheet which will allow you to order a Temperature or Temperature/Humidity Combination sensor.

Applications: Outside Air Temperature Sensing, Cold Storage Facilities, High Dew Point/Condensing Environments

The ACI Platinum Outside Air Series is covered by ACI's Five (5) Year Limited Warranty. The warranty can be found in the front of ACI's Sensors & Transmitters catalog, as well as on ACI's website, www.workaci.com.




PRODUCT SPECIFICATIONS

Sensor Type Sensor Curve:	Platinum RTD PTC (Positive Temperature Coefficient)
Number Sensing Points:	One
Number Wires:	A/100-2W-xx-O Series and A/1K-2W-xx-O Series: Two (Non-Polarity Sensitive) A/100-3W-xx-O Series and A/1K-3W-xx-O Series: Three (Polarity Sensitive)
Sensor Output @ 0°C (32°F):	A/100-xW-xx-O Series: 100 Ohms nominal A/1K-xW-xx-O Series: 1000 Ohms nominal
Sensor Accuracy @ 0°C (32°F):	+/- 0.06% Class A (Tolerance Formula: +/- °C = (0.15°C + (0.002 * t)) where t is the absolute value of Temperature above or below 0°C in °C) -40°C (-40°F): +/- 0.23°C (+/- 0.414°F) 0°C (32°F): +/- 0.15°C (+/- 0.27°F) 70°C (158°F): +/- 0.29°C (+/- 0.53°F)
Din Standard Temperature Coefficient:	DIN EN 60751 (IEC 751) 3850 ppm / °C
Sensor Stability:	+/- 0.03% after 1000 Hours @ 300°C (572°F)
Response Time (63% Step Change):	25 Seconds nominal
Self-Heating Maximum Operating Current:	100 Ohm RTD: 7 mW/°C (Still Air) 5 mA 1K Ohm RTD: 4mW/°C (Still Air) 3 mA
Operating Storage Temperature Range:	-40 to 70°C (-40 to 158°F) -40 to 70°C (-40 to 158°F)
Operating Humidity Range:	0 to 100% RH, Condensing
Enclosure Specifications (Temperature, Material, Flammability, NEMA/IP Ratings):	“-EH” Enclosure: PC/ASA Plastic w/ UV Protectant; -40 to 88°C (-40 to 190°F); UL94-V0 “-4X” Enclosure: Polystyrene Plastic, -40 to 70°C (-40 to 158°F), UL94-V2, NEMA 4X (IP 66) “-BB” Enclosure: Aluminum, -40 to 121°C (-40 to 250°F), NEMA 3R
Lead Length Conductor Size:	14” (35.6cm) 22 AWG (0.65mm)
Lead Wire Insulation Wire Rating:	Etched (PTFE) Teflon Colored Leads MIL-W-16878/4 (Type E)
Conductor Material:	Silver Plated Copper
Product Dimensions:	See Drawings on back of Data Sheet
Product Weight:	A/100/1K-xx-O-EH: 0.46 lbs. (0.21kg) A/100/1K-xx-O-4X: 0.38 lbs. (0.17kg) A/100/1K-xx-O-BB: 0.76 lbs. (0.35kg)
Agency Approvals:	CE, RoHS2, WEEE



DIMENSIONAL DRAWING. WEIGHTS

Bell Box Enclosure [BB]






xx = Sensor Type

Bell Box Enclosure [BB] Weight

ACI Model #	Weight
A/xx-O-BB	0.76 lbs. (0.172 kg)




Euro Enclosure [EH]



Euro Enclosure [EH] Weight

ACI Model #	Weight
A/xx-O-EH	0.46 lbs. (0.345 kg)

NEMA 4X Enclosure [4X]



NEMA 4X Enclosure [4X] Weight

ACI Model #	Weight
A/xx-Q-4X	0.38 lbs. (0.209 kg)

Front & Right Views

Top View

Product Weight

STANDARD ORDERING

Model # Example: A/100-2W-O-EH -OR- 125166


Model #	Item #	Description
A/100-2W-O-EH	125166	100 Ohm RTD, 2-Wire, Outside Air Sensor, Euro Enclosure, 14" Brown/Brown Leads
A/100-2W-O-BB	119961	100 Ohm RTD, 2-Wire, Outside Air Sensor, Aluminum Weather Proof Enclosure, 14" Brown/Brown Leads
A/100-2W-O-4X	135278	100 Ohm RTD, 2-Wire, Outside Air Sensor, NEMA 4X Weather Proof Enclosure, 14" Brown/Brown Leads
A/100-3W-O-EH	125178	100 Ohm RTD, 3-Wire, Outside Air Sensor, Euro Enclosure, 14" Brown/Brown/Black Leads
A/100-3W-O-BB	120044	100 Ohm RTD, 3-Wire, Outside Air Sensor, Aluminum Weather Proof Enclosure, 14" Brown/Brown/Black Leads
A/100-3W-O-4X	120043	100 Ohm RTD, 3-Wire, Outside Air Sensor, NEMA 4X Weather Proof Enclosure, 14" Brown/Brown/Black Leads
A/1K-2W-O-EH	125211	1K Ohm RTD, 2-Wire, Outside Air Sensor, Euro Enclosure, 14" Black/Black Leads
A/1K-2W-O-BB	120315	1K Ohm RTD, 2-Wire, Outside Air Sensor, Aluminum Weather Proof Enclosure, 14" Black/Black Leads
A/1K-2W-O-4X	119398	1K Ohm RTD, 2-Wire, Outside Air Sensor, NEMA 4X Weather Proof Enclosure, 14" Black/Black Leads
A/1K-3W-O-EH	125216	1K Ohm RTD, 3-Wire, Outside Air Sensor, Euro Enclosure, 14" Black/Black/White Leads
A/1K-3W-O-BB	142485	1K Ohm RTD, 3-Wire, Outside Air Sensor, Aluminum Weather Proof Enclosure, 14" Black/Black/White Leads
A/1K-3W-O-4X	131776	1K Ohm RTD, 3-Wire, Outside Air Sensor, NEMA 4X Weather Proof Enclosure, 14" Black/Black/White Leads

CUSTOM ORDERING

Model # Example:

A/	100	2W	O-EH	NIST
----	-----	----	------	------

MODEL

A. Sensor Series <i>No Selection Required</i>	A/ 	A/
B. Model Series <i>Select One (1)</i>	100 = 100 Ohm Platinum RTD 1K = 1K Ohm Platinum RTD	
C. Number of Wires <i>Select One (1)</i>	2W = Two Wires 3W = Three Wires	
D. Enclosure <i>Select One (1)</i>	O-EH = Euro Enclosure O-BB = Aluminum Enclosure O-4X = NEMA 4X Enclosure	
E. NIST <i>Select One (1)</i>	---- = No NIST Certificate NIST = NIST Certificate (3 Points)	