



Product Change Notice (PCN)

Date: **04/23/2026**

PCN Number: **PCN-0451534R-01**

To Our Customers:

We appreciate your use of our products. Our commitment in maintaining and improving processes is demonstrated by plans to enhance our product quality, reliability, and manufacturability. The purpose of this notice is to inform you of a product change.

Product(s) Affected: **PJ-067A & PJ-067B**

Reason(s) for Change: **Factory Location Change.**

Description of Change: **Mechanical, material and electrical differences as shown in the detail image below**

PREVIOUS SAME SKY DETAIL / IMAGE	NEW SAME SKY DETAIL / IMAGE

F-723-001

Revision: A

MATING PLUG
Jack Insertion Depth: 8.4mm

MATING PLUG
Jack Insertion Depth: 9.2 mm

	MATERIAL	PLATING
center pin	brass	nickel
terminal 1	brass	silver
terminal 2	phosphor bronze	silver
terminal 3	brass	silver
bushing	brass	nickel
insulator	red vulcanite fiber	
plastic	PBT	
nut	brass	nickel
washer	steel	nickel

DESCRIPTION	MATERIAL	PLATING/COLOR
center pin	brass	10 μ " min CuSn
terminal 1	brass	8 μ " min silver
terminal 2	phosphor bronze	8 μ " min silver
terminal 3	phosphor bronze	8 μ " min silver
bushing	brass	10 μ " min CuSn
insulator	bakelite	---
housing	PBT (UL94V-0)	black
nut	brass	40 μ " min nickel
washer	brass	40 μ " min nickel

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			24		vdc
rated input current			5		A
contact resistance			30		m Ω
insulation resistance	at 500 vdc	100			M Ω
voltage withstand	for 1 minute		500		Vac
insertion/withdrawal force		0.2	3.0		kgf
operating temperature		-25	70		°C
life			5,000		cycles

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated input voltage			24		vdc
rated input current			5		A
contact resistance			30		m Ω
insulation resistance	at 500 vdc	100			M Ω
voltage withstand	for 1 minute		500		Vac
insertion/withdrawal force		0.3	3.0		kgf
operating temperature		-25	70		°C
life			5,000		cycles

Affected Date Code: All orders placed after 05/11/2026

PCN Approval:

Operations/Quality



Product Management

