



PCN (Product Change Notice)

This document applies to all companies and branches of the Würth Elektronik eiSos Group.

- ☒ Major Change
☐ Minor Change

PCN Number: PCN_SwTASV_20260808 Affected Series: WS-TASV Affected Part Number: see table "PART NUMBER, REVISION & DATASHEET" PCN Date: 2026-05-08 (YYYY-MM-DD) Effective Date: 2026-08-08 (YYYY-MM-DD)	Change Category: ☐ Equipment/Location ☐ General Data ☐ Material ☐ Process ☒ Product Design ☐ Shipping/Packaging ☐ Supplier ☐ Software
Contact: Product Management Phone: +49 (0) 7942 - 945 5001 Fax: +49 (0) 7942 - 945 5179 E-Mail: pcn.eican@we-online.com	Datasheet Change: ☒ Yes ☐ No Attachment: ☐ Yes ☒ No

DESCRIPTION OF CHANGE:

In order to enhance the product reliability, Würth Elektronik eiSos will upgrade the rated current and voltage of products and correct tolerance of total height.

There will be no change in fit, form, function, quality or reliability of the product.

The storage conditions (in original packaging) specified in the datasheets have been updated according to DIN EN 61760-2.



The preliminary datasheets of the affected part numbers will be available on the website after the PCN date.
 Link to the website: [WS-TASV](#)

PART NUMBER, REVISION & DATASHEET:

Part Number	Revision before change	Revision after change
430773034825	002.000	003.000
430783034816	002.000	003.000
430753034832	001.000	002.000
430773051825	002.000	003.000
430783051816	002.000	003.000
430753051832	001.000	002.000

Note: the links in the table above remain valid until the effective date.

DETAILS OF CHANGE:

before change					after change				
Rated Current: 50mA Rated Voltage: 12V(DC)					Rated Current: 20mA Rated Voltage: 32V(DC)				
Properties	Test conditions	Value	Unit	Tol.	Properties	Test conditions	Value	Unit	Tol.
Rated Current	I_R	50	mA		Rated Current	I_R	20	mA	
Rated Voltage	V_R	12	V (DC)		Rated Voltage	V_R	32	V (DC)	
Tolerance of height: ± 0.1					Tolerance of height: ± 0.3				
									

RELIABILITY / QUALIFICATION OF CHANGE:

An additional reliability testing was performed and approved.

Qualification according to Würth Elektronik eiSos reliability standards.

Additional details of the tests can be found in the table below:

Test Item	Sample size	Reference	Test conditions	Acceptance
Operating Life	30	IEC61020-2009	Voltage: 32 VDC, Current: 20 mA Test Speed: 120 cycles per minute Force: following Datasheet specification Number of times: following Datasheet specification	Approved