

Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date:09 Jul 2026

Title of Change:	Qualification for SO8FL and u8FL Package from Mold Compound G700LS to G700LAE	
Proposed Changed Material First Ship Date:	29 May 2027 or earlier if approved by customer	
Current Material Last Order Date:	N/A <i>Orders received after the Current Material Last Order Date expiration are to be considered as orders for new changed material as described in this PCN. Orders for current (unchanged) material after this date will be per mutual agreement and current material inventory availability.</i>	
Current Material Last Delivery Date:	N/A <i>The Current Material Last Delivery Date may be subject to change based on build and depletion of the current (unchanged) material inventory.</i>	
Product Category:	Active components – Discrete components	
Contact information:	Contact your local onsemi Sales Office	
PCN Samples Contact:	Contact your local onsemi Sales Office to place sample order. Sample requests are to be submitted no later than 45 days after publication of this change notification. Samples delivery timing will be subject to request date, sample quantity and special customer packing/label requirements.	
Additional Reliability Data:	Contact your local onsemi Sales Office	
Type of Notification:	This is an Initial Product/Process Change Notification (IPCN) sent to customers. An IPCN is an advance notification about an upcoming change and contains general information regarding the change details and devices affected. It also contains the preliminary reliability qualification plan. The completed qualification and characterization data will be included in the Final Product/Process Change Notification (FPCN). This IPCN notification will be followed by a Final Product/Process Change Notification (FPCN) at least 6 months prior to implementation of the change. In case of questions, contact <PCN.Support@onsemi.com>	
Change Category		
Category	Type of Change	
Process - Assembly	SEM-PA-11: Change of mold compound / encapsulation material	
Description and Purpose:		
onsemi wishes to inform customers of its plan to change the mold compound used in SO8FL and u8FL packages from G700LS to G700LAE at the onsemi Seremban, Malaysia manufacturing site. This change is being implemented to improve delamination performance after preconditioning.		
	From	To
Mold Compound	G700LS	G700LAE
There are no product material changes as a result of this change and no product marking change as a result of this change.		
There is no product marking change as a result of this change		
Reason / Motivation for Change:	Process/Materials Change	
Anticipated impact on fit, form, function, reliability, product safety or manufacturability:	The device will be qualified and validated based on the same Product Specification. No anticipated impacts.	



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

Sites Affected:

onsemi Sites

onsemi Seremban, Malaysia

External Foundry/Subcon Sites

None

Marking of Parts/ Traceability of Change:

No change

Qualification Plan:

QV DEVICE NAME : NVMFD6H840NLT1G

RMS: 101329

PACKAGE: SO8FL Dual (T8)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMFD040N10MCLT1G

RMS: 102365

PACKAGE: SO8FL Dual (PTNG)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

QV DEVICE NAME : NVMFS3D6N10MCLT1G

RMS: 101197

PACKAGE: SO8FL HD (PTNG)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMFS5C604NLAFT1G

RMS: 101842

PACKAGE: SO8FL HD (T6)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
High Humidity High Temperature Reverse Bias	JESD22-A101	85°C, 85% RH, bias	1008 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

QV DEVICE NAME : NVMFS6H800NWFT1G

RMS: 104471

PACKAGE: SO8FL HD (T8)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTF56H850NLWFTAG

RMS: 104474

PACKAGE: u8FL (T8)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

QV DEVICE NAME : NVTFS9D6P04M8LTAG

RMS: 102571

PACKAGE: u8FL (MV8)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=90°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : MBR8170TFSTXG

RMS: 102572

PACKAGE: u8FL (Schottky)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=90°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
High Humidity High Temperature Reverse Bias	JESD22-A101	85°C, 85% RH, bias	1008 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NTMFS002P03P8ZST1G

RMS: 104088

PACKAGE: SO8FL HD (PT8P)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=150°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=150°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 150°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NRVB30H100MFST3G

RMS: 102309

PACKAGE: SO8FL HD (Schottky Planar)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=90°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C, mount form air to air	1000 cyc
High Humidity High Temperature Reverse Bias	JESD22-A101	85°C, 85% RH, bias	1008 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NRVTS30120MFST3G

RMS: 107925

PACKAGE: SO8FL HD (Trench Schottky)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=90°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C, mount form air to air	1000 cyc
High Humidity High Temperature Reverse Bias	JESD22-A101	85°C, 85% RH, bias	1008 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMFS5832NLWFT1G

RMS: 105752

PACKAGE: SO8FL HD (T2)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMF55113PLWFT1G

RMS: 107924

PACKAGE: SO8FL HD (T1)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : MBR30170MFST1G

RMS: 110767

PACKAGE: SO8FL HD (Schottky Diode)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=90°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTFWS015P03P8ZTAG

RMS: 106678

PACKAGE: u8FL (PT8P)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTFWS002N04CLTAG

RMS: 106421

PACKAGE: u8FL (T6)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTFWS027N10MCLTAG

RMS: 106696

PACKAGE: u8FL (PTNG)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTF5010N10MCLTAG

RMS: 106696

PACKAGE: u8FL (PTNG)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTFS5116PLWFTAG

RMS: 105753

PACKAGE: u8FL (T1)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NRVHP820MFD1G

PACKAGE: SO8FL Dual (Rect Ultrafast)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMFD5873NLWFT1G-UM

PACKAGE: SO8FL Dual (T2)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMFD5C650NLT1G-01

PACKAGE: SO8FL Dual (T6)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NTMFS0D8N02P1ET1G

PACKAGE: SO8FL HD (PT11E)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVMFS9D6P04M8LT1G

PACKAGE: SO8FL HD (MV8)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NVTFS5826NLWFTWG

PACKAGE: u8FL (T2)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Gate Bias	JESD22-A108	Ta=175°C, 100% max rated Vgss	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NRTS6100TFSTAG

PACKAGE: u8FL (Trench Schottky)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=175°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -55°C to +150°C, mount form air to air	1000 cyc
Highly Accelerated Stress Test	JESD22-A110	130°C, 85% RH, 18.8psig, bias	96 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

QV DEVICE NAME : NRVTS30120MFST3G

RMS: 107925

PACKAGE: SO8FL HD (Trench Schottky)

Test	Specification	Condition	Interval
High Temperature Reverse Bias	JESD22-A108	Ta=90°C, 100% max rated V	1008 hrs
High Temperature Storage Life	JESD22-A103	Ta= 175°C	1008 hrs
Preconditioning	J-STD-020 JESD-A113	MSL 1 @ 260 °C	
Intermittent Operating Life	MIL-STD-750 (M1037) AEC-Q101	Ta=+25°C, delta Tj=100°C On/off = 2 min	15000 cyc
Temperature Cycling	JESD22-A104	Ta= -65°C to +150°C, mount form air to air	1000 cyc
High Humidity High Temperature Reverse Bias	JESD22-A101	85°C, 85% RH, bias	1008 hrs
Unbiased Highly Accelerated Stress Test	JESD22-A118	130°C, 85% RH, 18.8psig, unbiased	96 hrs
Resistance to Solder Heat	JESD22- B106	Ta = 265°C, 10 sec	
Solderability	JSTD002	Ta = 245°C, 5 sec	
Physical Dimension	JESD22-B120		

Estimated date for qualification completion: **1 August 2026**

Electrical Characteristics Summary:

Electrical characteristics are not impacted.

List of Affected Parts:

Note: Only the standard (off the shelf) part numbers are listed in the parts list. Any custom parts affected by this PCN are shown in the customer specific PCN addendum in the PCN email notification, or on the [PCN Customized Portal](#).

Current Part Number	New Part Number	Qualification Vehicle
NVTF004N04CETAG	#NONE	NVTFWS002N04CLTAG
NVMFWS016N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS020N06CT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS021N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS024N06CT1G	#NONE	NVMFS3D6N10MCLT1G
NVTF005N04CTAG	#NONE	NVTFWS002N04CLTAG
NVTF010N10MCLTAG	#NONE	NVTFWS002N04CLTAG
NVTF016N06CTAG	#NONE	NVTFWS002N04CLTAG
NVTF020N06CTAG	#NONE	NVTFWS002N04CLTAG
NVTF024N06CTAG	#NONE	NVTFWS002N04CLTAG
NVTF027N10MCLTAG	#NONE	NVTFWS002N04CLTAG



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVTFS030N06CTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C02NTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C08NTWG	#NONE	NVTFWS002N04CLTAG
NVTFS4C13NETAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C13NETWG	#NONE	NVTFWS002N04CLTAG
NVTFS4C13NWFTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C305NETAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C306NTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C308NTAG	#NONE	NVTFWS002N04CLTAG
NVMFS4C03NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C310NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C05NT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C05NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C301NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C301NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C303NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C303NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C305NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C306NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C306NWEFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C308NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLWFHT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C406NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C406NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NWFAFT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C410NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C423NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C423NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NLT1G	#NONE	NVMFS5C604NLAFT1G
NVTFWS002N04CTAG	#NONE	NVTFWS002N04CLTAG
NRVB1240MFST1G	#NONE	NRVB30H100MFST3G
NRVB440MFSWFT1G	#NONE	NRVB30H100MFST3G
NVMFS5C628NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C645NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NLWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVTF55C466NLETAG	#NONE	NVTFWS002N04CLTAG
NRVB5H100MFST3G	#NONE	NRVTS30100MFST3G
NVMFS015N10MCLT1G	#NONE	NVMFS9D6P04M8LT1G
NVMFS016N06CT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS020N06CT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFS021N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFS4C01NT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLWFT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C442NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFAT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C466NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C466NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C612NLWFAT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C612NWFT1G	#NONE	NVMFS5C604NLAFT1G
NRVTS30100MFST3G	#NONE	NRVTS30100MFST3G
NVMFS024N06CT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C406NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NAFT1G	#NONE	NVMFS5C604NLAFT1G
NVTFWS002N04CLTAG	#NONE	NVTFWS002N04CLTAG
NVMFS5C426NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLWFAT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NLWFAT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NAFT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C442NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NLT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFWS027N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS040N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS3D6N10MCLT1G	#NONE	NVMFS5C604NLAFT1G
NVTFS002N04CLTAG	#NONE	NVMFS9D6P04M8LT1G
NVTFS002N04CTAG	#NONE	NVMFS9D6P04M8LT1G
NVTFS003N04CTAG	#NONE	NVTFWS002N04CLTAG
NVTFS008N04CTAG	#NONE	NVTFWS002N04CLTAG
NVTFS015N04CTAG	#NONE	NVTFWS002N04CLTAG
NVTFS040N10MCLTAG	#NONE	NVTFWS027N10MCLTAG
NVTFS070N10MCLTAG	#NONE	NVTFS9D6P04M8LTAG
NVTFS4C05NWFTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C06NTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C06NTWG	#NONE	NVTFWS002N04CLTAG
NVTFS4C08NTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C13NTWG	#NONE	NVTFWS002N04CLTAG
NVTFS4C25NTAG	#NONE	NVTFWS002N04CLTAG
NVTFS4C25NWFTAG	#NONE	NVTFWS002N04CLTAG
NVTFS5124PLTAG	#NONE	NVTFS5116PLWFTAG
NVTFS5124PLTWG	#NONE	NVTFS5116PLWFTAG
NVTFS5124PLWFTAG	#NONE	NVTFS5116PLWFTAG
NVMFS4C03NWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C03NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C05NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C302NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C302NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C302NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C305NT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS4C306NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C308NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C310NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5826NLWFT1G	#NONE	NVMFS5113PLWFT1G
NVMFS5C404NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C420NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C423NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVTF5C680NLWFTAG	#NONE	NVTFWS002N04CLTAG
NVTFWS010N10MCLTAG	#NONE	NVTFWS002N04CLTAG
NVMFS5C442NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NRVB10100MFST1G	#NONE	NRVB30H100MFST3G
NRVB2045MFST1G	#NONE	NRVB30H100MFST3G
NRVB30H100MFST1G	#NONE	NRVB30H100MFST3G
NRVB440MFSWFT3G	#NONE	NRVHP820MFD1G
NVMFS5C628NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C628NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C628NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C628NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C638NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C645NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C645NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NLAFT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C670NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C673NLT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C673NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C673NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVTF55C453NLETAG	#NONE	NVTFWS002N04CLTAG
NVTF55C453NLWFTAG	#NONE	NVTFWS002N04CLTAG
NVTF55C454NLTAG	#NONE	NVTFWS002N04CLTAG
NVTF55C466NLWFTAG	#NONE	NVTFWS002N04CLTAG
NVTF55C471NLTAG	#NONE	NVTFWS002N04CLTAG
NVTF55C478NLTAG	#NONE	NVTFWS002N04CLTAG
NVTF55C670NLTAG	#NONE	NVTFWS002N04CLTAG
NVTF55C673NLTWG	#NONE	NVTFWS002N04CLTAG
NVTF55C680NLTAG	#NONE	NVTFWS002N04CLTAG
NRVB460MFST1G	#NONE	NRVB30H100MFST3G
NRVB5100MFST1G	#NONE	NRVB30H100MFST3G
NRVB540MFST1G	#NONE	NRVB30H100MFST3G
NRVB560MFST1G	#NONE	NRVB30H100MFST3G
NRVB560MFST3G	#NONE	NRVB30H100MFST3G
NRVB8H100MFSWFT1G	#NONE	NRVHP820MFD1G
NRVB8H100MFSWFT3G	#NONE	NRVHP820MFD1G
NRVTS30120MFST3G	#NONE	NRVTS30100MFST3G
NRVTS3060MFST3G	#NONE	NRVTS30100MFST3G
NRVTS8H120EMFST1G	#NONE	NRVTS30100MFST3G
NVMFS005N10MCLT1G	#NONE	NVTF56H850NLWFTAG
NVMFS016N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFS027N10MCLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS040N10MCLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C01NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C01NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C03NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NLAFT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C450NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C466NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C466NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NLWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C468NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C612NLET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C612NLT1G	#NONE	NVMFS5C604NLAFT1G
NRVB30H100MFST3G	#NONE	NRVB30H100MFST3G
NVMFS3D6N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFS5C404NAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NT1G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C404NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C406NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NWF3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NWF3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C680NLT1G	#NONE	NVMFS5C604NLAFT1G
NRVB2045EMFST1G	#NONE	NRVB30H100MFST3G
NVMFS5C673NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C423NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C423NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NLT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C673NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NRVB2045EMFST3G	#NONE	NRVB30H100MFST3G
NVMFS4C05NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C677NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C680NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C682NLAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C682NLWFAFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C682NLWFAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFWS002N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS003N10MCT1G	#NONE	NVMFS3D6N10MCLT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFWS015N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFS5C673NWFT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C682NLT3G	#NONE	NVMFS5C604NLAFT1G
NVMFWS004N10MCT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS005N10MCLT1G	#NONE	NVMFS3D6N10MCLT1G
NVMFWS016N06CT1G	#NONE	NVMFS3D6N10MCLT1G
NVTF55C680NLETAG	#NONE	NVTFWS002N04CLTAG
NVMFS5C670NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLWFHT1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C645NLWFT1G	#NONE	NVMFS5C604NLAFT1G
NVTFWS010N10MCTAG	#NONE	NVTFWS002N04CLTAG
NVMFS4C301NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C302NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C303NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C305NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NWFHT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C430NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C450NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C646NLET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C670NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C673NLAFT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C301NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C303NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C404NLWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C406NET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C410NLWFHT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C426NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C442NWFHT3G	#NONE	NVMFS5C604NLAFT1G



Initial Product/Process Change Notification

Document #: IPCN26343ZB

Issue Date: 09 Jul 2026

NVMFS5C450NWFHT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NLWFHT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C456NWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C460NLWFHT3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C604NLET3G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C612NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS5C628NLWFET1G	#NONE	NVMFS5C604NLAFT1G
NVMFS4C302NWFHT1G	#NONE	NVMFS5C604NLAFT1G

PCN Product List Addendum for:

Customer Contact Name: Premier Farnell Dropbox

Customer Contact Email: productchangenotices@newark.com

Appendix A: Changed Products

PCN#: IPCN26343ZB
Issue Date: Jul 09, 2026

NWKC: PREMIER FARNELL

Product	Customer Part Number	Qualification Vehicle	New Part Number	Replacement Supplier
NVTFS4C305NETAG	4843839	NVTFWS002N04CLTAG	#NONE	
NVMFS4C05NWFET1G	4843829	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C404NLWFAFT1G	2760520	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C420NLT1G	3677741	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C420NLWFT1G	3677742	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C420NT1G	3677743	NVMFS5C604NLAFT1G	#NONE	
NVTFS5C466NLETAG	4843842	NVTFWS002N04CLTAG	#NONE	
NVTFS4C02NTAG	3677745	NVTFWS002N04CLTAG	#NONE	
NVTFS4C13NETAG	4843838	NVTFWS002N04CLTAG	#NONE	
NVMFS5C426NLT1G	2895703	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C456NT1G	2895744	NVMFS5C604NLAFT1G	#NONE	
NVMFS015N10MCLT1G	3528520	NVMFS9D6P04M8LT1G	#NONE	
NVMFS5C612NWFET1G	3367868	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C442NLAFT1G	3368867	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C604NLWFET1G	4904486	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C430NLAFT1G	3368866	NVMFS5C604NLAFT1G	#NONE	
NVTFS4C05NWFETAG	3368876	NVTFWS002N04CLTAG	#NONE	
NVMFS5C420NWFET1G	3677744	NVMFS5C604NLAFT1G	#NONE	
NVTFS5124PLTAG	2724439	NVTFS5116PLWFTAG	#NONE	
NVMFS5C426NAFT1G	3368864	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C628NLT1G	3003946	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C423NLWFET1G	4843833	NVMFS5C604NLAFT1G	#NONE	
NVTFS5C680NLWFTAG	3368879	NVTFWS002N04CLTAG	#NONE	
NVMFS5C628NWFET1G	3367870	NVMFS5C604NLAFT1G	#NONE	
NVTFS5C453NLWFTAG	2775455	NVTFWS002N04CLTAG	#NONE	
NVMFS5C645NLWFAFT1G	3368873	NVMFS5C604NLAFT1G	#NONE	
NVTFS5C453NLETAG	4843841	NVTFWS002N04CLTAG	#NONE	
NVTFS5C453NLWFTAG	2985477	NVTFWS002N04CLTAG	#NONE	
NVTFS5C670NLTAG	3003891	NVTFWS002N04CLTAG	#NONE	
NVMFS040N10MCLT1G	4257652	NVMFS5C604NLAFT1G	#NONE	
NVMFS4C01NT1G	3368861	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C460NLAFT1G	3368869	NVMFS5C604NLAFT1G	#NONE	
NVMFS4C03NT1G	3368862	NVMFS5C604NLAFT1G	#NONE	
NVMFS3D6N10MCLT1G	3528521	NVMFS3D6N10MCLT1G	#NONE	
NVMFS5C612NLET1G	4843835	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C404NT1G	2508379	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C680NLT1G	2895757	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C604NLWFAFT1G	2760522	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C460NLWFAFT1G	3368870	NVMFS5C604NLAFT1G	#NONE	
NVMFS5C604NLAFT1G	2760521	NVMFS5C604NLAFT1G	#NONE	
NVMFWS003N10MCT1G	4317988	NVMFS3D6N10MCLT1G	#NONE	