Product Change Notice (PCN)

Date: 07/13/2026

PCN Number: PCN-0485197R-01

To Our Customers:
We appreciate your use of our products. Our commitment in maintaining and improving processes is demonstrated by plans to enhance our product quality, reliability, and manufacturability. The purpose of this notice is to inform you of a product change.

Product(s) Affected: *CPM1208 Series (CPM1208-02A-02-MRA-M9-67, CPM1208-03A-02-MRA-M9-67, CPM1208-04A-02-MRA-M9-67, CPM1208-05A-02-MRA-M9-67, CPM1208-05B-02-MRA-M9-67, CPM1208-08A-02-MRA-M9-67, CPM1208-12A-02-MRA-M9-67, CPM1208-17A-02-MRA-M9-67)*

Reason(s) for Change: *Factory Location Change, New Tooling, Manufacturing Process Improvement*

Description of Change:

Mechanical differences

- Previous operating temperature -25, new operating temperature -40

Visual differences shown below

6405 SW Rosewood St, Ste C | Lake Oswego, OR 97035 | sameskydevices.com | 877.323.3576

same sky

PREVIOUS SAME SKY DETAIL / IMAGE	NEW SAME SKY DETAIL / IMAGE
	
	

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated voltage	2, 3, & 4 pole models 5 pole models 8, 12 & 17 pole models			250 60 30	V V V
rated current	2, 3, 4, & 5 pole models 8 pole model 12 & 17 pole models			4 2 1.5	A A A
withstanding voltage	for 1 minute, 2, 3, & 4 pole models 5 pole models 8 , 12 & 17 pole models		2,500 1,500 800		Vac Vac Vac
contact resistance				5	mΩ
insulation resistance	at 500 Vdc for 1 minute	100			MΩ
insertion force	2, 3, 4 & 5 pole models 8 & 12 pole models 17 pole model			1.0 2.3 3.0	kgf kgf kgf
withdrawal force	2, 3, 4 & 5 pole models 8, 12 & 17 pole models			1.5 3.0	kgf kgf
operating temperature		-25		80	°C
life		500			cycles
flammability rating	see material table				
RoHS	yes				
IP level	IP67 (in mated condition)				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	for 1-3 seconds	430		450	°C

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated voltage	2, 3, & 4 pole models 5 pole models 8, 12 & 17 pole models			250 60 30	V V V
rated current	2, 3, 4, & 5 pole models 8 pole model 12 & 17 pole models			4 2 1.5	A A A
withstanding voltage	for 1 minute, 2, 3, & 4 pole models 5 pole models 8 , 12 & 17 pole models		2,500 1,500 800		Vac Vac Vac
contact resistance				5	mΩ
insulation resistance	at 500 Vdc for 1 minute	100			MΩ
operating temperature		-40		80	°C
life		500			cycles
flammability rating	see material table				
RoHS	yes				
IP level	IP67 (in mated condition)				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	for 1-3 seconds	430		450	°C

Affected Date Code: All orders placed after **07/09/2026**

PCN Approval:

Operations/Quality

Product Management

Revision: A