

RoHS
Compliant



Features

- Narrow viewing angle.

Applications

- Automotive: backlighting in dashboard and switch
- Telecommunication: indicator and backlighting in telephone and fax
- Flat backlight for LCD switch and symbol

Specifications

Dimensions	: 1.6mm × 0.8mm × 0.95mm.
Emitted colour	: Green
Dice	: (InGaN)
Lens colour	: Water clear

Absolute Maximum Ratings: (T_A = 25°C)

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	100	mW
Forward current	I _F	25	mA
Peak Forward Current*1	I _{FP}	100	
Reverse Voltage	V _R	5	V
Operating Temperature	T _{OPR}	-40°C to +85°C	
Storage Temperature	T _{STG}		

Notes:

*1: Pulse width ≤ 0.1ms, Duty cycles ≤ 1/10

Optical / Electrical Characteristics at T_A = 25°C


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Forward Voltage (one circuit)	V _F	I _F =20mA	2.8	-	3.6	V
Reverse Current (one circuit)	I _R	V _R =5V	-	-	10	uA
Dominate Wavelength	λ _D	I _F =20mA	518	-	530	nm
Luminous Intensity	I _V		4250	-	7300	mcd
Viewing Angle	2θ _{1/2}		-	30	-	Deg.

Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity or dominate wavelength), the typical accuracy of the sorting process is as follows:


- Dominate Wavelength: ±1nm
- Luminous Intensity: (plus/minus 15)%
- Forward Voltage: plus/minus 0.1 * V

Package Outlines




Dimensions : Millimetres (Inches)


Typical Electrical/Optical Characteristics Curves



Ambient Temperature VS. Relative Intensity
Ta-IV



Radiation Diagram



Part Number Table

Description	Part Number
Single Colour LED, 0603, 30D, Green	MP017029

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.