Ettus USRP X410 Specifications

2026-11-16

Contents

Ettus USRP X410 Specifications 3

Ettus USRP X410 Specifications

Ettus USRP X410 Specifications

These specifications apply to the Standard FPGA and the Locked FPGA variants of the Ettus USRP X410.

Revision History

Version	Date changed	Description
378493H-01	September 2026	Updated applicability to include Locked FPGA variants.
378493G-01	May 2025	Added maximum input power footnote.
378493F-01	February 2025	Added device pinout.
378493E-01	November 2024	Updated NVM footnote.
378493D-01	March 2024	Updated power supply, environmental, and physical specifications.
378493C-01	July 2023	Updated device weight and RX input power graph.
378493B-01	May 2022	Updated current and power specifications.
378493A-01	June 2021	Initial release.

Looking For Something Else?

For information not found in the specifications for your product, such as operating instructions, browse *Related Information*.

Related information:

- Getting Started Guide
- User Manual

- Software and Driver Downloads
- Dimensional Drawings
- Product Certifications
- Letter of Volatility
- Knowledgebase
- Discussion Forums
- NI Learning Center

Definitions

Warranted specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

Characteristics describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- *Typical* specifications describe the performance met by a majority of models.
- *Nominal* specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are *Characteristics* unless otherwise noted.

Conditions

Specifications are valid at 23 °C ± 5 °C unless otherwise noted.

Ettus USRP X410 Pinout

Figure 1. Front Panel



Table 1. Front Panel Connector Descriptions

Conector	Description
TX/RX 0	Output and input terminal for the RF signal. TX/RX 0 is an SMA (f)

Conector	Description
	connector with an impedance of 50 Ω and is a single-ended input or output channel.
RX 1	Input terminal for the RF signal. RX 1 is an SMA (f) connector with an impedance of 50 Ω and is a single-ended input channel.
GPIO 0, GPIO 1	General Purpose Input/Output (GPIO) digital terminals. GPIO 0 and GPIO 1 are HDMI Type-A connectors. Output voltage can be configured per individual connector, either 1.8 V (default), 2.5 V, or 3.3 V.

Individual connectors not within a larger grouping of connectors are named according to their label on the front panel. Individual connectors within a grouping of connectors are named according to the convention *DB Label: Grouping Label: Connector Label*. For example:

- **GPIO 0**—The individual connector on the Ettus USRP X410 front panel labeled *GPIO 0*
- **DB 0: RF 0: TX/RX 0**—The individual connector on the Ettus USRP X410 front panel labeled *TX/RX 0* within the group of connectors on the device labeled *RF 0* in the *DB 0* area

Key Specifications

Table 2. Key Specifications

RF capabilities	4 TX, 4 RX, independently tunable Superheterodyne architecture 1 MHz to 7.2 GHz, tunable up to 8 GHz Up to 400 MHz bandwidth per channel
Processing system (PS)	Quad Core ARM Cortex-A53 (1200 MHz) 4 GB DDR4

Programmable logic (PL)	FPGA: RFSoC ZU28DR 2 × 4 GB DDR4
Software	UHD version 4.1 or later RFNoC GNU Radio C/C++ Python OpenEmbedded Linux on A53 NI-USRP 20.8 or later LabVIEW 2020 or later LabVIEW FPGA 2020 or later
Synchronization	REF IN (clock reference input) PPS IN (PPS time reference) TRIG IN/OUT GPSDO included OCXO included
Digital interfaces	2 QSFP28 (10/100 GbE, Aurora)[1] 2 iPass+ zHD (cabled PCIe Gen3 x8)[2] Ethernet (1 GbE to PS) 2 USB-C (USB to PS, Console/JTAG)

	2 HDMI (GPIO)
Power, form factor	12 V DC, 16 A maximum Half-wide RU 28.5 cm × 22.2 cm × 4.4 cm (11.2 in. × 8.7 in. × 1.7 in.)

Controller

Processing System

Table 3. Processing System

CPU	Quad Core ARM Cortex-A53 (1200 MHz)
Memory	4 GB DDR4, 2.4 GT/s
NVM[3]	32 GB eMMC (Pseudo SLC)
RJ45	1 GbE host connection
USB-C	USB to PS (USB 2.0) USB Console/JTAG

Programmable Logic

Table 4. Programmable Logic

FPGA	Xilinx RFSoC XCZU28DR Speed Grade -1
Memory	2 × 4 GB DDR4, 2.4 GT/s
SD-FEC	8 dedicated SD-FEC cores

1. 100 GbE is supported in the UHD Toolflow. Aurora streaming is supported in the LabVIEW FPGA Toolflow. Support for these capabilities is not available in UHD 4.1. It will be added in a subsequent release.
2. This feature is supported in the LabVIEW FPGA Toolflow.
3. Module assembly H and earlier has an NVM of 16 GB. All other module assemblies have an NVM of 32 GB.

QSFP28	2 × 4 lanes 10/100 GbE, Aurora[4]
iPass+ zHD	2 × 4 lanes PCIe Gen3x8[5]
GPIO	2 HDMI 12 I/O lines per connector Maximum data rate 100 Mbps Selectable I/O voltage (3.3 V, 2.5 V, or 1.8 V)
Trigger	SMA: Trigger In/Out (3.3 V I/O voltage)

Baseband

Table 5. Baseband

Maximum I/Q sample rates[6]	491.52 MSps 500.00 MSps
Number of available channels	4
ADC resolution	12 bit
DAC resolution	14 bit

4. 100 GbE is supported in the UHD Toolflow. Aurora streaming is supported in the LabVIEW FPGA Toolflow. Support for these capabilities is not available in UHD 4.1. It will be added in a subsequent release.
5. This feature is supported in the LabVIEW FPGA Toolflow.
6. The applicable maximum value depends on the sample rate selected in software.

RF Transmitter

Table 6. Transmitter

Number of channels	4
Frequency range	1 MHz to 7.2 GHz, tunable up to 8 GHz[7]
Frequency step	<1 Hz
Maximum output power[8]	<23 dBm
TX/RX settling time	0.3 µs[9]
TX gain settling time	1 µs
Gain range[10]	60 dB, nominal
Gain step	1 dB, nominal

Table 7. TX Phase Noise, 1 GHz Carrier Frequency, 23 °C, Nominal

1 kHz offset	-91 dBc/Hz
10 kHz offset	-101 dBc/Hz
100 kHz offset	-103 dBc/Hz

Table 8. Bandwidth and Noise Density

Maximum instantaneous real-time bandwidth	400 MHz
Average noise density (23 °C, 10 MHz to 8 GHz)[11]	-146 dBm/Hz

7. Tuning the frequency to values >7.2 GHz may degrade output power, TX EVM, noise density, and noise figure specifications.
8. Maximum output power varies by frequency. Refer to the subsequent *TX Measurements* section for additional information.
9. This settling time applies to the TX/RX switch.
10. The output power resulting from the gain setting varies over the frequency band and among devices.
11. Measured at the TX gain setting required to reach 0 dBm output power with 0 dBFS baseband signal.

TX Measurements

Figure 2. TX EVM Bathtub Curves: 5GNR, UL, FDD, SISO, 100 MHz BW, 30 kHz SCS, 256 QAM, 23 °C ± 5 °C



Figure 3. TX Maximum Output Power: 0 dBFS CW, Maximum Gain Setting, 23 °C ± 5 °C



Note The previous figure depicts the average TX maximum output power based on 4 units with 16 channels total measured at 18 °C, 23 °C, and 28 °C. The bars represent 80% confidence intervals at selected frequencies.

RF Receiver

Table 9. Receiver

Number of channels	4
Frequency range	1 MHz to 7.2 GHz, tunable up to 8 GHz
Frequency step	<1 Hz

Table 10. Gain Range

≤500 MHz	38 dB, nominal
>500 MHz	60 dB, nominal

Note The *gain range* is the received signal amplitude resulting from the gain setting varies over the frequency band and among devices.

Table 11. Gain Step

Gain step	1 dB, nominal

Table 12. Maximum Input Power, Damage Level

≤3 GHz	+14 dBm continuous
>3 GHz	+17 dBm continuous, +20 dBm for up to 5 minutes

Table 13. Maximum Operating Power

Maximum operating power[12]	0 dBm

Notice It is sometimes necessary to use attenuation when connecting multiple Ettus USRP X410 devices or when creating a loopback connection to avoid damaging the hardware.

Table 14. RX Gain Settling Time

RX gain settling time	0.3 µs

Table 15. Noise Figure

500 MHz to 3.1 GHz	8 dB

12. *Maximum operating power* refers to the maximum input power at the RF input port that does not saturate the ADC. The ADC can become saturated when the input power is greater than the maximum operating power. You can input a CW tone at maximum operating power at any frequency. You can configure gain settings at all frequencies to allow input signals at the maximum operating power to avoid saturating the ADC.

3.1 GHz to 6 GHz	6.5 dB
6 GHz to 8 GHz	9 dB

Table 16. Input and Bandwidth

Input IP3, 0 dBm input, full scale	+12 dBm
Maximum instantaneous real-time bandwidth	400 MHz

RX Measurements

Figure 4. RX EVM Bathtub Curves: 5GNR, UL, FDD, SISO, 100 MHz BW, 30 kHz SCS, 256 QAM, 23 °C ± 5 °C



Figure 5. RX Input Power to Reach 0 dBFS: CW Input, 30 dB Gain Setting, 23 °C ± 5 °C



Note The previous figure depicts the average RX input power to reach 0 dBFS based on 4 units with 16 channels total measured at 18 °C, 23 °C, and 28 °C. The bars represent 80% confidence intervals at selected frequencies.

GPS Disciplined Oscillator (GPSDO)

Table 17. Frequency Accuracy

OCXO (not locked to GPS)[13]	2.5 ppm
OCXO (locked to GPS)	5 ppb

Note *Frequency accuracy* is based on oven-controlled crystal oscillator (OCXO) vendor specifications and is not measured. Alternatively, you can incorporate an external reference source to provide a more precise frequency Reference Clock and to achieve better frequency accuracy.

Table 18. Active Antenna

Voltage	3.3 V
Power	0.19 W
Frequency band(s)	L1, C/A 1.574 GHz

Power

Notice The protection provided by this product may be impaired if it is used in a manner not described in this document.

Table 19. Power

Voltage rating	12 V
Frequency rating	DC
Current/power rating	7 A to 16 A (bitfile dependent)
Power supply	190 W, minimum

13. Factory default accuracy. Contact NI if your application requires tuning the OCXO output frequency.

Caution The product must be powered with an AC adapter offered by NI that meets the power requirements for the product and has appropriate safety certification marks for country of use.

Physical Characteristics

Dimensions and Weight

Table 20. Dimensions and Weight

Dimensions, enclosure	26.7 cm × 22.2 cm × 4.4 cm (10.5 in. × 8.7 in. × 1.7 in.)
Dimensions, enclosure and connectors	28.5 cm × 22.2 cm × 4.4 cm (11.2 in. × 8.7 in. × 1.7 in.)
Weight	2.7 kg (6 lb)

Ventilation Clearance and Cooling

This product is designed to operate on a bench or in an instrument rack. Fan vents are located at the back of the product. Standard airflow provision of the product is set up as front to back cooling with option to change the airflow direction in the interest for directing back to front cooling using a fan cartridge accessory.

Adequate clearance is required at the front and back of the product and surrounding equipment, inclusive of indiscriminate heat generating devices, and any potential air flow blockages must be maintained to ensure proper cooling.

Table 21. Ventilation Clearance and Cooling

Minimum cooling clearances	51 mm (2 in.) at the front and back

Note Benchtop and rack mount applications may require additional cooling clearances for optimal airflow and to reduce any unexpected hot air recirculation in either direction of the air inlet fans.

Environment

Environmental Characteristics

Table 22. Environmental Characteristics

Operating temperature range	0 °C to 55 °C
Storage temperature range	-40 °C to 71 °C
Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Operating humidity range	10% to 90%, noncondensing
Storage humidity range	5% to 95%, noncondensing
Pollution Degree	2

Indoor use only.

Environmental Standards

This product meets the requirements of the following environmental standards for electrical equipment.

- IEC 60068-2-1 Cold
- IEC 60068-2-2 Dry heat
- IEC 60068-2-78 Damp heat (steady state)
- IEC 60068-2-64 Random vibration
- IEC 60068-2-27 Shock

Note To verify marine approval certification for a product, refer to the product label or visit `ni.com/certification` and search for the certificate.

Shock and Vibration

Table 23. Shock and Vibration

Operating vibration	5 Hz to 500 Hz, 0.3 g RMS
Non-operating vibration	5 Hz to 500 Hz, 2.4 g
RMS operating shock	30 g, half-sine, 11 ms pulse
Non-operating shock	50 g, half-sine, 11 ms pulse

© 2026 National Instruments Corporation.