


Tri Rated 1.5MM



Features:

- Heat resisting PVC insulated.
- CK type.
- Tri-rated.
- UL style 1015; CSA type TEW; BS6231.

Specifications:

Conductor:

1.5mm² (16AWG) (32/0.24mm*) plain annealed copper bunch meeting the requirements of BS6360, class 5. UL subject 758, CSA standard C22.2 no.127.

Minimum cross-sectional area : 1.27mm².
Maximum lay of bunch : 50.8mm.
Maximum resistance at 20°C : 13.3Ω/km.

Insulation:

PVC compound meeting the requirements of type T13 to BS EN 50363.

Class 43 PVC to UL1581, class 28 to CSA standard C22.2 no.127.

Minimum thickness at any one point : 0.69mm (UL/CSA).
Minimum average thickness : 0.8mm (BS).
Minimum overall diameter : 3.0mm (BS).
Maximum overall diameter : 3.6mm (BS).
Lay up : Not applicable.
Screen : Not applicable.
Sheath : Not applicable.

* This is a nominal number of strands.

* All wires made to meet minimum cross-sectional area and maximum resistance as set in BS specification.

Part Number Table

Description	Part Number
Wire, Tri Rated, Black, 1.5mm, 100m	CBBR0191
Wire, Tri Rated, Blue, 1.5mm, 100m	CBBR0192
Wire, Tri Rated, Brown, 1.5mm, 100m	CBBR0193
Wire, Tri Rated, Grey, 1.5mm, 100m	CBBR0195
Wire, Tri Rated, Orange, 1.5mm, 100m	CBBR0196
Wire, Tri Rated, Red, 1.5mm, 100m	CBBR0198
Wire, Tri Rated, White, 1.5mm, 100m	CBBR0200
Wire, Tri Rated, Yellow, 1.5mm, 100m	CBBR0201
Wire, Tri Rated, Green/Yellow, 1.5mm, 100m	CBBR0202

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC pro-Power is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

