



The EasyPAT 1600 is a legal minimum tester suitable for high speed low cost testing.

It preserves the 2100's speed of use and simplicity and is an ideal PAT for those needing to do the legal minimum as quickly as possible.

- Does both mandatory tests and has a built in fuse test
- 25A, 8A and 100mA (for computers, etc) earth bond tests selectable with a simple rocker switch
- Incorporates an extension lead tester to test IEC leads (can also be used to test 110V extension leads with a MAREX331 adaptor).

## SPECIFICATIONS 1 of 2

### ELECTRICAL

**Supply Voltage:** 230V±10% 50/60Hz

**Power Consumption:** 10/220VA

### EARTH CONTINUITY TEST (8A & 25A)

**Test Voltage:** 6V AC nominal with no load

**Test Current:** 25A AC nom @ 0.1Ω (25A), 8A AC nom @ 0.1Ω (8A)

**Display Range:** 0 - 1.99Ω

**Accuracy of Indication:** ±10% of reading ±2 digits

### EARTH CONTINUITY TEST (100MA)

**Test Voltage:** 130mV DC nominal open circuit

**Test Current:** 100mA DC nominal constant current

**Range:** 0 - 1.99Ω

**Accuracy of Indication:** ±10% of reading ±2 digit

### INSULATION TEST

**Test Voltage:** 500V DC -0% +20% at 0.5MΩ

**Short Circuit Current:** 1.5mA DC nominal

**Display Range:** 0 - 19.9MΩ

**Accuracy Of Indication:** ±5% of reading ±1 digit

### FUSE TEST

**Test Voltage:** 6V AC nominal

**Over range threshold:** 10kΩ nominal

**Zero range threshold:** 800kΩ nominal

### LEADS

**Mains:** 1.7M fixed lead, with a 13A moulded plug

**Earth Continuity:** 3M long, detachable lead, heavy duty crocodile/alligator clip.

**230V IEC Adaptor:** 13A BS1363 plug to IEC320 connector, 230mm long.

### SOCKETS

**Mains:** 230V 13A to BS 1363

110V 16A to BS4343

**Leadtest:** IEC320

CONT...



## SPECIFICATIONS *CONT 2 of 2*

### LAMPS

**Over Temperature:** Red LED which illuminates when the temperature limit for the instrument has been exceeded. LED extinguishes when unit cools.

**Lamp 1/ Lamp 2:** Red LED's which illuminate to indicate lead 'polarity' for extension lead test facility.

### FUSES

**Plug:** 13A 1" HBC (Ceramic)  
**Internal:** 3.15A (F) 5x20mm, HBC (Ceramic)  
Internal fuse is not user replaceable.

### Safety

**EMC:** Meets BS EN 50081-1  
BS EN 50082-1  
**LVD:** Meets BS EN 61010-1

### MECHANICAL SPECIFICATION - CASE

**Size:** 330x263x144mm  
**Material:** ABS/Polycarbonate  
**Colour:** Yellow/Black  
**Weight:** 4kg nominal

### ENVIRONMENTAL SPECIFICATION - TEMPERATURE

**Operating:** 0 °C to 35°C  
**Storage:** -10 °C to 50°C

This instrument has been designed to be used in a clean dry environment.

Do not use the instrument outdoors or in wet conditions.