



The Dataman 848Pro2 is a super fast stand-alone gang programmer with eight independent 48-pin ZIF sockets, ISP capabilities and internal control PC driven by Windows XP Embedded. The 848Pro2 is built to meet the demands of super fast high volume production programming with minimal operator effort.

Supporting over 51,000 (Jan 2010) devices with new support added monthly, the Dataman 848Pro2 can program without the need for family-specific modules, giving you the freedom to choose the optimal device for your design. Independent programming options combine with device insertion tests and a user friendly interface to give higher programming yields and reduced failure rates.

Hardware

General

- The 848Pro2 programmer offers the same advanced features as the 848Pro+ programmer but with up to 70% faster programming of high-capacity memory devices.
- FPGA based totally reconfigurable 48 powerful TTL pindrivers provide H/L/pull_up/pull_down and read capability for each pin of the socket. Advanced pindrivers incorporate high-quality high-speed circuitry to deliver signals without overshoot or ground bounce for all supported devices. Pin drivers operate down to 1.8V so you'll be ready to program the full range of tomorrow's advanced low-voltage devices.
- Each programming module performs device insertion tests and contact checks before it programs each device. These capabilities, supported by overcurrent protection and signature-byte check, help prevent chip damage due to operator error.
- Selftest capability allows diagnostics in the software to thoroughly check the health of the programmer.
- Built-in protection circuits eliminate damage to programming modules and/or programmed devices due to environment or operator failure. All ZIF sockets and ISP connector pins are protected against ESD up to 15kV.
- The 848Pro2 programmer performs programming verification at the marginal levels of supply voltage, improving programming yield and guaranteeing long data retention.
- Wide range of socket converters are available to handle devices in PLCC, SOIC, PSOP, SSOP, TSOP, TSSOP, TQFP, QFN (MLF), SDIP, BGA and other packages.

- Stand-alone operation with touch screen control
- Internal control PC driven by Windows XP Embedded
- Up to 70% faster programming of high-capacity memory devices
- Over 51,000 (Jan 2010) devices supported with new devices added monthly
- Independent modules supporting concurrent programming
- Intelligent pin drivers operate down to 1.8V so you'll be ready to program the full range of tomorrow's advanced low-voltage devices
- ISP capable using the JTAG interface
- Comprehensive 3 years parts and labour warranty
- Free life-time software updates

Programmer Specification

- 8 x universal programming modules (8 x 48-pin DIL ZIF sockets and 8 x ISP connectors)
- Power and operation status LEDs
- Banana jack for ESD wrist strap connection
- Banana jack for connection to ground

Module Specification

Base Unit (DAC)

- On-board intelligence: powerful microprocessor and FPGA based state machine
- Three D/A converters for VCCP, VPP1, and VPP2, controllable rise and fall time
- VCCP range 0..8V/1A
- VPP1, VPP2 range 0..26V/1A
- Selftest capability

ZIF Socket

- 48-pin DIL ZIF socket accepts both 300/600 mil devices up to 48-pin
- Pindrivers: 48 universal
- VCCP/VPP1/VPP2 can be connected to each pin
- Perfect ground for each pin
- FPGA based TTL driver provides H, L, CLK, pull-up, pull-down on all pindriver pins
- Analog pindriver output level selectable from 1.8V up to 26V
- Current limitation, overcurrent shutdown, power failure shutdown
- ESD protection on each pin (IEC1000-4-2: 15kV air, 8kV contact)
- Continuity test: each pin is tested before every programming operation

ISP Connector

- 20-pin male type with missinsertion lock
- 6 TTL pindrivers, provides H, L, CLK, pull-up, pull-down; level H selectable from 1.8V up to 5V to handle all (including low-voltage) devices
- 1x VCCP voltage (range 2V..7V/100mA), can be applied to two pins
- Programmed chip voltage (VCCP) with both source/sink capability and voltage sense
- 1x VPP voltage (range 2V..25V/50mA), can be applied to six pins
- Target system supply voltage (range 2V..6V/250mA)
- ESD protection on each pin (IEC1000-4-2: 15kV air, 8kV contact)
- Input signal, switch YES! equivalent (active level: max. 0.8V)

Software:

User Interface

There are two ways to control and monitor the 848Pro2 programmer:

- The graphical control unit with touch screen provides essential information about the programming flow and allows basic control of the 848Pro2
- Using a display, keyboard and mouse allows access to all programming flow information and options.

Production Mode Control

- This part of the software is focused to the easy monitoring of high-volume production operations.
- Operator-friendly control software combines many powerful functions with ease of use. Graphic user interface provides an overview of important information, reducing the burden on the operator with unnecessary details.



- Project files are used to control the 848Pro2 and contain user data, chip programming setup, chip configuration, auto programming command sequence. This helps minimize operator error as the project file is normally created by an engineer and then passed to the operator. The optional protected mode can be set avoiding unwanted changes to the project file.
- Each chip may be programmed with different data such as serial number, configuration and calibration information.

Engineering Mode Control

- This part of the software is focused to the quick and easy preparation of the project file for usage in the production mode control software.
- Each programming module is driven by an easy-to-use control program. Selecting a device is performed by its class, by manufacturer or simply by typing a fragment of the vendor name and/or part number.
- Standard device-related commands (read, blank check, program, verify, erase) are enhanced by test functions (insertion test, signature-byte check) and additional special functions (auto-increment serialisation, production mode - programming starts immediately after chip is inserted).
- All known data formats are supported. Automatic file format detection and conversion performed during loading of file.
- The software provides extensive information about programmable devices including detailed drawings of all available packages. The software also provides explanations of chip labelling (prefixes and suffixes).

The Dataman 848Pro2 supports over 51,000 (Jan 2010) of the most popular devices in use today - with new devices being added monthly. Dataman 848Pro2 coverage includes the following device types:

Programmer (ZIF Socket)

EPROM, EEPROM, Flash EPROM, NAND Flash, LBA-NAND, mDOC H3, multi-chip devices, FRAM, MRAM, NV RAM, PROM, Serial E(E)PROM, Serial Flash, Configuration (EE)PROM, 1-Wire E(E)PROM, PLD, FPGA, Clocks, Microcontrollers

Programmer (ISP Connector)

Serial E(E)PROM, 1-Wire E(E)PROM, Serial Flash, Microcontrollers, PLD, FPGA

Package Includes:

Dataman 848Pro2 Stand-Alone Production Programmer

Processor: Intel Core 2 Quad 2.66GHz
Operating system: Windows XP Embedded
Dimensions: 625 x 465 x 115mm (24.6 x 18.3 x 4.5inches)
Weight: 14.9kg (32.85lb)
Operating voltage: 100-240V AC
Power consumption: max. 300W active

- ISP cable (x8)
- Diagnostic POD for selftest of the programmer (x1)
- Diagnostic POD for selftest of the ISP connector (x1)
- Anti-dust cover for ZIF socket (x8)
- ESD wrist strap with cord and banana plug
- Vacuum pen
- User manual
- Software
- Optional range of adapters and socket converters also available

Warranty and Support

- 30 day money back guarantee* - If you don't like it, send it back.
- Three year guarantee - Three years parts and labour warranty, on the 848Pro2 universal gang programmer.
- Life-Time Technical Support - 848Pro2 technical support is available free via our website and telephone helpdesk for life.
- Life-Time Software Updates - 848Pro2 software updates are available free via our website for life.

*Applies to orders from UK/US offices only

www.dataman.com

IN THE UK...

Dataman Programmers Ltd.
Station Road, Maiden Newton
Dorset DT2 0AE, UK
Tel (01300) 320719
Fax (01300) 321012

IN THE US...

Dataman Inc.
215 East Michigan Avenue
Orange City, Florida 32763 USA
Tel (386) 774-7785
Fax (386) 774-7796

Available from...