


REVISIONS				BY DATE	APP'D. DATE
R. SYM.	ECO NO.	DESCRIPTION			
C	1637	CORRECT PRINT		1637	1637

JOTES:

1. WHEN ASSEMBLED, PINS SHOULD PROTRUDE .052 ± .002 FROM POSITIONER BODY.
2. BREAK SHARP EDGES .005 R. MAX.
3. ✓ FINISH ALL OVER.



"STAMP "M22520/7-02"

SEE NOTE 1.

ITEM	PART NO.	REQ'D	DESCRIPTION
7	1-1176	1	6-32 X 3/32 FL PT. SET SCR
6	6-1048	2	.043 DIA X .129 PIN
5	8-1036	1	SPRING
4	1-1015	1	1/4-28 X 1/8 JAM SCREW
3	MH750-136DS-6	1	BODY (GREEN)
2	8G-1S-DP	1	DATAPLATE
1	MH750-439	1	INSERT

MATERIAL	CHICKEN	DATE - 2-28-84	DMC DANIELS MANUFACTURING CO. ORLANDO, FLORIDA SC# 1185	DATE
MATERIAL	CHICKEN	DATE - 2-28-84	POSITIONER (M12252017-02)	DATE
TOLERANCE		PART NO. 81-1185		
Uniform dimension throughout part no. 1185. Angle = 17°		WHT SCALL	INCHES	MM
Dimensions:		X - 0.70	.065	.018
		X - .010	.005	.001
		X - .005	.002	.001
		X - .002	.001	.0005
		REMOVABLE BURRS & BRISTLES SHOULD NOT EXCEED .005 INCH		
FINISH: PLATING		PART NO. 81-1185		

This document is furnished by DANIELS MANUFACTURING COMPANY and describes certain non-disclosing understandings and agreements. No disclosure of this document to third parties or copying thereof is permitted without the express written consent of the parties. This document is the property of DANIELS MANUFACTURING COMPANY and contains confidential information which is the sole property of DANIELS MANUFACTURING COMPANY. Any unauthorized disclosure or copying of this document will result in damages to DANIELS MANUFACTURING COMPANY.