

TECHNICAL DATA

Model: MB060D050 UGS/E+

page:2

Standard Specification: () EN61558-1:1998

Client Number :

Sample No :

Model Number: MB060D050UGS/E+

Type : Single-Voltage AC/DC Adaptor :

1. Electrical Data

Input □□	Input Voltage/Frequency □□□□□/□□□	230V~50Hz
	Input Power □□□□□□	7.9W
Output □□	Rated Output Voltage □□□□□□□□	6V
	Rated Output Load Current □□□□□□□□	500mA
	Rated Output Power □□□□□□□□	3VA
Resistance □□	Insulation Resistance □□□□□□	100M□(measured with 500 DC Voltage)
Protection □□□□	Thermal Protection □□□□□□	Thermal fuse:125□/2A
	Withstand Voltage (Hi-Pot) □□□□	AC 3750V 50Hz for 1minute or AC 4000V 2seconds

2. Mechanical Data

Supply Connection Type □□□□□	U
Primary Turns & Wire Gauge □□□□□□□□□	3220T/0.09mm
Secondary Turns & Wire Gauge □□□□□□□□□	115T/0.45mm
Core Size □□□□□□	41x 16 (mm)
Output Plug Dimensions □□□□□□□	5.5X2.1/12(mm)
Polarity □□□□	CENTRE POSITIVE
Unit Weight □□□□	234g
Dimensions □□□□□□	60 x 50 x 81(mm)

3. Output Voltage

Sample □□	Unload output current □□□□□□□□ _____0_____ mA		Full-load output current □□□□□□□□ _____500_____ mA	
	Output Voltage □□□□□□	Ripple Voltage □□□□□□	Output Voltage □□□□□□	Voltage Range □ □□□□□
1	9.69V	-----	6.12V	5.4-6.6V

Test by: □□□□□ □□□ Checked by: □□□□□ □□□ Date: □□□□ 2004/09/10



MINWA (CHINA) ELECTRONICS MANUFACTURE CO.,LTD

Model: MB060D050 UGS/E+

TECHNICAL DATA

page:2

2	9.71V	-----	6.09V	5.4-6.6V
---	-------	-------	-------	----------